



SIMATIC S7-1200, Analog input, SB 1231, 1 AI, +/-10 V DC (12 bit resol.) or 0-20 mA

General information	
Product type designation	SB 1231, AI 1x12 bit
Supply voltage	
Rated value (DC)	24 V
Input current	
from backplane bus 5 V DC, typ.	55 mA
Power loss	
Power loss, typ.	0.4 W
Analog inputs	
Number of analog inputs	1; Current or voltage differential inputs
permissible input voltage for current input (destruction limit), max.	±35 V
permissible input voltage for voltage input (destruction limit), max.	35 V
permissible input current for voltage input (destruction limit), max.	40 mA
permissible input current for current input (destruction limit), max.	40 mA
Cycle time (all channels) max.	156.25 µs; 400 Hz suppression
Input ranges	
<ul style="list-style-type: none"> <li>• Voltage</li> <li>• Current</li> <li>• Thermocouple</li> <li>• Resistance thermometer</li> <li>• Resistance</li> </ul>	Yes; ±10V, ±5V, ±2.5V Yes; 0 to 20 mA No No No
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>• -10 V to +10 V — Input resistance (-10 V to +10 V)</li> <li>• -2.5 V to +2.5 V — Input resistance (-2.5 V to +2.5 V)</li> <li>• -5 V to +5 V — Input resistance (-5 V to +5 V)</li> </ul>	Yes ≥9 MOhm Yes ≥9 MOhm Yes ≥9 MOhm
Input ranges (rated values), currents	
<ul style="list-style-type: none"> <li>• 0 to 20 mA — Input resistance (0 to 20 mA)</li> </ul>	Yes ≥ 250 Ohm
Analog outputs	
Number of analog outputs	0
Cable length	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	100 m; shielded, twisted pair
Analog value generation for the inputs	

Measurement principle	integrating
<b>Integration and conversion time/resolution per channel</b>	
<ul style="list-style-type: none"> <li>Resolution with overrange (bit including sign), max.</li> <li>Integration time, parameterizable</li> <li>Interference voltage suppression for interference frequency f1 in Hz</li> </ul>	11 bit; + sign Yes 40 dB, DC to 60 Hz
<b>Smoothing of measured values</b>	
<ul style="list-style-type: none"> <li>parameterizable</li> <li>Step: None</li> <li>Step: low</li> <li>Step: Medium</li> <li>Step: High</li> </ul>	Yes Yes Yes Yes Yes
<b>Errors/accuracies</b>	
Temperature error (relative to input range), (+/-)	25 °C ±0.3%, to 55 °C ±0.6% total measurement range
<b>Interrupts/diagnostics/status information</b>	
Alarms	Yes
Diagnostics function	Yes
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> </ul>	Yes
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>Wire-break</li> </ul>	No
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>for status of the inputs</li> <li>for maintenance</li> </ul>	Yes Yes
<b>Standards, approvals, certificates</b>	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
<b>Ambient conditions</b>	
<b>Free fall</b>	
<ul style="list-style-type: none"> <li>Fall height, max.</li> </ul>	0.3 m; five times, in product package
<b>Ambient temperature during operation</b>	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> <li>horizontal installation, min.</li> <li>horizontal installation, max.</li> <li>vertical installation, min.</li> <li>vertical installation, max.</li> </ul>	-20 °C 60 °C -20 °C 60 °C -20 °C 50 °C
<b>Ambient temperature during storage/transportation</b>	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>	-40 °C 70 °C
<b>Air pressure acc. to IEC 60068-2-13</b>	
<ul style="list-style-type: none"> <li>Operation, min.</li> <li>Operation, max.</li> <li>Storage/transport, min.</li> <li>Storage/transport, max.</li> </ul>	795 hPa 1 080 hPa 660 hPa 1 080 hPa
<b>Relative humidity</b>	
<ul style="list-style-type: none"> <li>Operation at 25 °C without condensation, max.</li> </ul>	95 %
<b>Pollutant concentrations</b>	
<ul style="list-style-type: none"> <li>SO2 at RH &lt; 60% without condensation</li> </ul>	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free
<b>connection method / header</b>	
required front connector	Yes
<b>Mechanics/material</b>	
Enclosure material (front)	

- Plastic

Yes

#### Dimensions

Width	38 mm
Height	62 mm
Depth	21 mm

#### Weights

Weight, approx.	35 g
-----------------	------

**last modified:**

2/9/2021 