



SIMATIC HMI, KTP400 Basic, Basic Panel, Key/touch operation, 4" TFT display, 65536 colors, PROFINET interface, configurable from WinCC Basic V13/ STEP 7 Basic V13, contains open-source software, which is provided free of charge see enclosed CD

| General information   |  |
|---|--|
| Product type designation  | KTP400 Basic                             |
| Display   |  |
| Design of display   | TFT widescreen display, LED backlighting |
| Screen diagonal   | 4.3 in                                   |
| Display width   | 95 mm                                    |
| Display height  | 53.9 mm                                  |
| Number of colors  | 65 536                                   |
| Resolution (pixels)   |  |
| • Horizontal image resolution   | 480 pixel                                |
| • Vertical image resolution   | 272 pixel                                |
| Backlighting  |  |
| • MTBF backlighting (at 25 °C)  | 20 000 h                                 |
| • Backlight dimmable  | Yes                                      |
| Control elements  |  |
| Keyboard fonts  |  |
| • Function keys   |  |
| — Number of function keys   | 4  |
| — Number of function keys with LEDs                                   | 0  |
| • Keys with LED   | No                                       |
| • System keys   | No                                       |
| • Numeric keyboard  | Yes; Onscreen keyboard                   |
| • alphanumeric keyboard   | Yes; Onscreen keyboard                   |
| Touch operation   |  |
| • Design as touch screen  | Yes; Analog-resistive                    |
| Installation type/mounting  |  |
| Mounting position   | vertical                                 |
| Wall mounting/direct mounting   | No                                       |
| Mounting in portrait format possible                                  | Yes                                      |
| Mounting in landscape format possible                                 | Yes                                      |
| maximum permissible angle of inclination without external ventilation | 35°                                      |
| Supply voltage  |  |
| Type of supply voltage  | DC                                       |
| Rated value (DC)  | 24 V                                     |
| permissible range, lower limit (DC)                                   | 19.2 V                                   |
| permissible range, upper limit (DC)                                   | 28.8 V                                   |
| Input current   |  |
| Current consumption (rated value)                                     | 125 mA                                   |

|  |   |
|--|---|
| Starting current inrush I <sup>2</sup> t         | 0.2 A <sup>2</sup> ·s                   |
| <b>Power</b>                                     |   |
| Active power input, typ.                         | 3 W                                     |
| <b>Processor</b>                                 |   |
| Processor type                                   | ARM                                     |
| <b>Memory</b>                                    |   |
| Flash  | Yes                                     |
| RAM  | Yes                                     |
| Memory available for user data                   | 10 Mbyte                                |
| <b>Type of output</b>                            |   |
| Acoustics  |   |
| • Buzzer   | Yes                                     |
| • Speaker  | No                                      |
| <b>Time of day</b>                               |   |
| Clock  |   |
| • Hardware clock (real-time)                     | Yes                                     |
| • Software clock                                 | Yes                                     |
| • retentive                                      | Yes; Back-up duration typically 6 weeks |
| • synchronizable                                 | Yes                                     |
| <b>Interfaces</b>                                |   |
| Number of industrial Ethernet interfaces         | 1                                       |
| Number of RS 485 interfaces                      | 0                                       |
| Number of RS 422 interfaces                      | 0                                       |
| Number of RS 232 interfaces                      | 0                                       |
| Number of USB interfaces                         | 1; Up to 16 GB                          |
| Number of 20 mA interfaces (TTY)                 | 0                                       |
| Number of parallel interfaces                    | 0                                       |
| Number of other interfaces                       | 0                                       |
| Number of SD card slots                          | 0                                       |
| With software interfaces                         | No                                      |
| <b>Industrial Ethernet</b>                       |   |
| • Industrial Ethernet status LED                 | 2                                       |
| <b>Protocols</b>                                 |   |
| PROFINET   | Yes                                     |
| Supports protocol for PROFINET IO                | No                                      |
| IRT  | No                                      |
| PROFIBUS   | No                                      |
| EtherNet/IP                                      | Yes                                     |
| MPI  | No                                      |
| <b>Protocols (Ethernet)</b>                      |   |
| • TCP/IP   | Yes                                     |
| • DHCP   | Yes                                     |
| • SNMP   | Yes                                     |
| • DCP  | Yes                                     |
| • LLDP   | Yes                                     |
| <b>WEB characteristics</b>                       |   |
| • HTTP   | No                                      |
| • HTML   | No                                      |
| <b>Redundancy mode</b>                           |   |
| Media redundancy                                 |   |
| — MRP  | No                                      |
| <b>Further protocols</b>                         |   |
| • CAN  | No                                      |
| • MODBUS   | Yes; Modicon (MODBUS TCP/IP)            |
| <b>Interrupts/diagnostics/status information</b> |   |
| <b>Diagnoses</b>                                 |   |
| • Diagnostic information readable                | No                                      |
| <b>EMC</b>                                       |   |
| Emission of radio interference acc. to EN 55 011 |   |

|   |                       |
|---|-----------------------|
| <ul style="list-style-type: none"> <li>• Limit class A, for use in industrial areas</li> </ul>  | Yes                   |
| <ul style="list-style-type: none"> <li>• Limit class B, for use in residential areas</li> </ul> | No                    |
| <b>Degree and class of protection</b>   |                       |
| IP (at the front)   | IP65                  |
| IP (rear)   | IP20                  |
| NEMA (front)  |                       |
| <ul style="list-style-type: none"> <li>• Enclosure Type 4 at the front</li> </ul>               | Yes                   |
| <ul style="list-style-type: none"> <li>• Enclosure Type 4x at the front</li> </ul>              | Yes                   |
| <b>Standards, approvals, certificates</b>   |                       |
| CE mark   | Yes                   |
| cULus   | Yes                   |
| RCM (formerly C-TICK)   | Yes                   |
| KC approval   | Yes                   |
| <b>Use in hazardous areas</b>   |                       |
| <ul style="list-style-type: none"> <li>• ATEX Zone 2</li> </ul>                                 | No                    |
| <ul style="list-style-type: none"> <li>• ATEX Zone 22</li> </ul>                                | No                    |
| <ul style="list-style-type: none"> <li>• IECEx Zone 2</li> </ul>                                | No                    |
| <ul style="list-style-type: none"> <li>• IECEx Zone 22</li> </ul>                               | No                    |
| <ul style="list-style-type: none"> <li>• cULus Class I Zone 1</li> </ul>                        | No                    |
| <ul style="list-style-type: none"> <li>• cULus Class I Zone 2, Division 2</li> </ul>            | No                    |
| <ul style="list-style-type: none"> <li>• FM Class I Division 2</li> </ul>                       | No                    |
| <b>Marine approval</b>  |                       |
| <ul style="list-style-type: none"> <li>• Germanischer Lloyd (GL)</li> </ul>                     | Yes                   |
| <ul style="list-style-type: none"> <li>• American Bureau of Shipping (ABS)</li> </ul>           | Yes                   |
| <ul style="list-style-type: none"> <li>• Bureau Veritas (BV)</li> </ul>                         | Yes                   |
| <ul style="list-style-type: none"> <li>• Det Norske Veritas (DNV)</li> </ul>                    | Yes                   |
| <ul style="list-style-type: none"> <li>• Lloyds Register of Shipping (LRS)</li> </ul>           | Yes                   |
| <ul style="list-style-type: none"> <li>• Nippon Kaiji Kyokai (Class NK)</li> </ul>              | Yes                   |
| <ul style="list-style-type: none"> <li>• Polski Rejestr Statkow (PRS)</li> </ul>                | No                    |
| <ul style="list-style-type: none"> <li>• Chinese Classification Society (CCS)</li> </ul>        | No                    |
| <b>Ambient conditions</b>   |                       |
| Suited for indoor use   | Yes                   |
| Suited for outdoor use  | No                    |
| <b>Ambient temperature during operation</b>   |                       |
| Operation (vertical installation)   |                       |
| — For vertical installation, min.   | 0 °C                  |
| — For vertical installation, max.   | 50 °C                 |
| Operation (max. tilt angle)   |                       |
| — At maximum tilt angle, min.   | 0 °C                  |
| — At maximum tilt angle, max.   | 40 °C                 |
| Operation (vertical installation, portrait format)  |                       |
| — For vertical installation, min.   | 0 °C                  |
| — For vertical installation, max.   | 40 °C                 |
| Operation (max. tilt angle, portrait format)  |                       |
| — At maximum tilt angle, min.   | 0 °C                  |
| — At maximum tilt angle, max.   | 35 °C                 |
| <b>Ambient temperature during storage/transportation</b>  |                       |
| <ul style="list-style-type: none"> <li>• min.</li> </ul>  | -20 °C                |
| <ul style="list-style-type: none"> <li>• max.</li> </ul>  | 60 °C                 |
| <b>Relative humidity</b>  |                       |
| <ul style="list-style-type: none"> <li>• Operation, max.</li> </ul>                             | 90 %; no condensation |
| <b>Operating systems</b>  |                       |
| proprietary   | Yes                   |
| pre-installed operating system  |                       |
| <ul style="list-style-type: none"> <li>• Windows CE</li> </ul>                                  | No                    |
| <b>configuration / header</b>   |                       |
| Message indicator   | Yes                   |
| Alarm system (incl. buffer and acknowledgment)  | Yes                   |
| Process value display (output)  | Yes                   |

|  |   |
|--|---|
| Process value default (input) possible                       | Yes   |
| Recipe management  | Yes   |
| <b>Configuration software</b>                                |   |
| • STEP 7 Basic (TIA Portal)                                  | Yes; via integrated WinCC Basic (TIA Portal)                  |
| • STEP 7 Professional (TIA Portal)                           | Yes; via integrated WinCC Basic (TIA Portal)                  |
| • WinCC flexible Compact                                     | No  |
| • WinCC flexible Standard                                    | No  |
| • WinCC flexible Advanced                                    | No  |
| • WinCC Basic (TIA Portal)                                   | Yes   |
| • WinCC Comfort (TIA Portal)                                 | Yes   |
| • WinCC Advanced (TIA Portal)                                | Yes   |
| • WinCC Professional (TIA Portal)                            | Yes   |
| <b>Languages</b>   |   |
| <b>Online languages</b>                                      |   |
| • Number of online/runtime languages                         | 10  |
| <b>Project languages</b>                                     |   |
| • Languages per project                                      | 32  |
| <b>Functionality under WinCC (TIA Portal)</b>                |   |
| Libraries  | Yes   |
| Applications/options   |   |
| • Web browser  | Yes   |
| • SIMATIC WinCC Sm@rtServer                                  | Yes; Available with WinCC (TIA Portal) V14 or higher          |
| Number of Visual Basic Scripts                               | No  |
| Task planner   | Yes   |
| • time-controlled  | No  |
| • task-controlled  | Yes   |
| Help system  | Yes   |
| • Number of characters per info text                         | 500   |
| <b>Message system</b>  |   |
| • Number of alarm classes                                    | 32  |
| • Bit messages   |   |
| — Number of bit messages                                     | 1 000   |
| • Analog messages  |   |
| — Number of analog messages                                  | 25  |
| • S7 alarm number procedure                                  | No  |
| • System messages HMI  | Yes   |
| • System event, more (SIMATIC S7, SINUMERIK, SIMOTION, ... ) | Yes; System message buffer of the SIMATIC S7-1200 and S7-1500 |
| • Number of characters per message                           | 80  |
| • Number of process values per message                       | 8   |
| • Acknowledgment groups                                      | Yes   |
| • Message indicator  | Yes   |
| • Message buffer   |   |
| — Number of entries  | 256   |
| — Circulating buffer   | Yes   |
| — retentive  | Yes   |
| — maintenance-free   | Yes   |
| <b>Recipe management</b>                                     |   |
| • Number of recipes  | 50  |
| • Data records per recipe                                    | 100   |
| • Entries per data record                                    | 100   |
| • Size of internal recipe memory                             | 256 kbyte   |
| • Recipe memory expandable                                   | No  |
| <b>Variables</b>   |   |
| • Number of variables per device                             | 800   |
| • Number of variables per screen                             | 100   |
| • Limit values   | Yes   |
| • Multiplexing   | Yes   |
| • Structures   | No  |
| • Arrays   | Yes   |

| Images                                 |   |
|--|---|
| • Number of configurable images        | 250   |
| • Permanent window/default             | Yes   |
| • Global image                         | Yes   |
| • Pop-up images                        | No  |
| • Slide-in images                      | No  |
| • Image selection by PLC               | Yes   |
| • Image number in the PLC              | Yes   |
| Image objects                          |   |
| • Number of objects per image          | 100   |
| • Text fields                          | Yes   |
| • I/O fields                           | Yes   |
| • Graphic I/O fields (graphics list)   | Yes   |
| • Symbolic I/O fields (text list)      | Yes   |
| • Date/time fields                     | Yes   |
| • Switches                             | Yes   |
| • Buttons                              | Yes   |
| • Graphic display                      | Yes   |
| • Icons                                | Yes   |
| • Geometric objects                    | Yes   |
| Complex image objects                  |   |
| • Number of complex objects per screen | 10  |
| • Alarm view                           | Yes   |
| • Trend view                           | Yes   |
| • User view                            | Yes   |
| • Status/control                       | No  |
| • Sm@rtClient view                     | No  |
| • Recipe view                          | Yes   |
| • f(x) trend view                      | No  |
| • System diagnostics view              | Yes; System message buffer of the SIMATIC S7-1200 and S7-1500 |
| • Media Player                         | No  |
| • HTML browser                         | Yes   |
| • PDF display                          | No  |
| • IP camera display                    | No  |
| • Bar graphs                           | Yes   |
| • Sliders                              | No  |
| • Pointer instruments                  | No  |
| • Analog/digital clock                 | No  |
| Lists                                  |   |
| • Number of text lists per project     | 300   |
| • Number of entries per text list      | 100   |
| • Number of graphics lists per project | 100   |
| • Number of entries per graphics list  | 100   |
| Archiving                              |   |
| • Number of archives per device        | 2; One message and one process value archive                  |
| • Number of entries per archive        | 10 000  |
| • Message archive                      | Yes   |
| • Process value archive                | Yes   |
| • Archiving methods                    |   |
| — Sequential archive                   | Yes   |
| — Short-term archive                   | Yes   |
| • Memory location                      |   |
| — Memory card                          | No  |
| — USB memory                           | Yes   |
| — Ethernet                             | No  |
| • Data storage format                  |   |
| — CSV                                  | No  |
| — TXT                                  | Yes   |
| — RDB                                  | No  |
| Security                               |   |

|  |                            |
|--|----------------------------|
| • Number of user groups                                | 50                         |
| • Number of user rights                                | 32                         |
| • Number of users                                      | 50                         |
| • Password export/import                               | Yes                        |
| • SIMATIC Logon  | No                         |
| <b>Character sets</b>                                  |                            |
| • Keyboard fonts                                       |                            |
| — US English   | Yes                        |
| <b>Transfer (upload/download)</b>                      |                            |
| • MPI/PROFIBUS DP                                      | No                         |
| • USB  | No                         |
| • Ethernet   | Yes                        |
| • using external storage medium                        | Yes                        |
| <b>Process coupling</b>                                |                            |
| • S7-1200  | Yes                        |
| • S7-1500  | Yes                        |
| • S7-200   | Yes                        |
| • S7-300/400   | Yes                        |
| • LOGO!  | Yes                        |
| • WinAC  | Yes                        |
| • SINUMERIK  | Yes; No access to NCK data |
| • SIMOTION   | Yes                        |
| • Allen Bradley (EtherNet/IP)                          | Yes                        |
| • Allen Bradley (DF1)                                  | No                         |
| • Mitsubishi (MC TCP/IP)                               | Yes                        |
| • Mitsubishi (FX)                                      | No                         |
| • OMRON (FINS TCP)                                     | No                         |
| • OMRON (LINK/Multilink)                               | No                         |
| • Modicon (Modbus TCP/IP)                              | Yes                        |
| • Modicon (Modbus)                                     | No                         |
| <b>Service tools/configuration aids</b>                |                            |
| • Backup/Restore manually                              | Yes                        |
| • Backup/Restore automatically                         | No                         |
| • Simulation   | Yes                        |
| • Device switchover                                    | Yes                        |
| <b>Peripherals/Options</b>                             |                            |
| Printer  | No                         |
| SIMATIC HMI MM memory card: Multi Media Card           | No                         |
| SIMATIC HMI SD memory card: Secure Digital memory card | No                         |
| SIMATIC HMI CF memory card Compact Flash Card          | No                         |
| USB memory   | Yes                        |
| SIMATIC IPC USB Flashdrive (USB stick)                 | Yes                        |
| SIMATIC HMI USB stick                                  | Yes                        |
| <b>Mechanics/material</b>                              |                            |
| Enclosure material (front)                             |                            |
| • Plastic  | Yes                        |
| • Aluminum   | No                         |
| • Stainless steel                                      | No                         |
| <b>Dimensions</b>                                      |                            |
| Width of the housing front                             | 141 mm                     |
| Height of housing front                                | 116 mm                     |
| Mounting cutout, width                                 | 123 mm                     |
| Mounting cutout, height                                | 99 mm                      |
| Overall depth  | 33 mm                      |
| <b>Weights</b>   |                            |
| Weight (without packaging)                             | 360 g                      |
| Weight (with packaging)                                | 470 g                      |

last modified:

10/8/2021 

