



Electronics module for ET 200S, 8DI 24 V DC 15 mm width, 1 unit per packing unit

Figure similar

Supply voltage	
Rated value (DC)	24 V; From power module
Reverse polarity protection	Yes
Input current	
from supply voltage L+, max.	Dependent on encoder
from backplane bus 3.3 V DC, max.	10 mA
Encoder supply	
Number of outputs	0; no encoder supply
Power loss	
Power loss, typ.	1.2 W
Address area	
Address space per module	
• Address space per module, max.	1 byte
Digital inputs	
Number of digital inputs	8
Input characteristic curve in accordance with IEC 61131, type 1	Yes; 2-wire sensors connectable
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5 V
• for signal "1"	+15 to +30 V
Input current	
• for signal "1", typ.	5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	2 ms
— at "0" to "1", max.	4.5 ms
— at "1" to "0", min.	2 ms
— at "1" to "0", max.	4.5 ms
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor),	1.5 mA

max.

#### Interrupts/diagnostics/status information

Diagnostics function No

#### Diagnostics indication LED

- Status indicator digital input (green) Yes

#### Parameter

Remark 3-byte parameter (not accessible for the user)

#### Potential separation

##### Potential separation digital inputs

- between the channels No
- between the channels and backplane bus Yes

#### Isolation

Isolation tested with 500 V DC

#### Dimensions

Width 15 mm

Height 81 mm

Depth 52 mm

#### Weights

Weight, approx. 35 g

**last modified:** 2/9/2021 