




SIMATIC ET 200SP, Digital input module, DI 8x 24V DC Basic, type 2 (IEC 61131), sink input, (PNP, P-reading), Packing unit: 1 piece, fits to BU-type A0, Colour Code CC01, input delay time 0,05..20ms, module diagnostics for: supply voltage

| General information | |
|--|--|
| Product type designation | DI 8x24VDC BA |
| HW functional status | FS03 |
| Firmware version | V0.0 |
| <ul style="list-style-type: none"> FW update possible | No |
| usable BaseUnits | BU type A0 |
| Color code for module-specific color identification plate | CC01 |
| Product function | |
| <ul style="list-style-type: none"> I&M data | Yes; I&M0 to I&M3 |
| <ul style="list-style-type: none"> Isochronous mode | No |
| Engineering with | |
| <ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version | V14 |
| <ul style="list-style-type: none"> STEP 7 configurable/integrated from version | V5.5 SP3 / - |
| <ul style="list-style-type: none"> PROFIBUS from GSD version/GSD revision | One GSD file each, Revision 3 and 5 and higher |
| <ul style="list-style-type: none"> PROFINET from GSD version/GSD revision | GSDML V2.3 |
| Operating mode | |
| <ul style="list-style-type: none"> DI | Yes |
| <ul style="list-style-type: none"> Counter | No |
| <ul style="list-style-type: none"> Oversampling | No |
| <ul style="list-style-type: none"> MSI | No |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |
| Input current | |
| Current consumption, max. | 70 mA; All channels are supplied from the encoder supply |
| Encoder supply | |
| Number of outputs | 8 |
| Output voltage, min. | 19.2 V |
| Short-circuit protection | Yes; per module |
| 24 V encoder supply | |
| <ul style="list-style-type: none"> 24 V | Yes |
| <ul style="list-style-type: none"> Short-circuit protection | Yes |
| <ul style="list-style-type: none"> Output current per channel, max. | 700 mA |
| <ul style="list-style-type: none"> Output current per module, max. | 700 mA |
| Power loss | |
| Power loss, typ. | 1.6 W; 24 V, 8 inputs supplied via encoder supply |

| Address area | |
|---|---|
| Address space per module | |
| • Inputs | 1 byte |
| Hardware configuration | |
| Automatic encoding | Yes |
| • Mechanical coding element | Yes |
| • Type of mechanical coding element | Type A |
| Selection of BaseUnit for connection variants | |
| • 1-wire connection | BU type A0 |
| • 2-wire connection | BU type A0 |
| • 3-wire connection | BU type A0 with AUX terminals or potential distributor module |
| • 4-wire connection | BU type A0 + Potential distributor module |
| Digital inputs | |
| Number of digital inputs | 8 |
| Digital inputs, parameterizable | Yes |
| Source/sink input | P-reading |
| Input characteristic curve in accordance with IEC 61131, type 1 | Yes |
| Input characteristic curve in accordance with IEC 61131, type 2 | Yes |
| Input characteristic curve in accordance with IEC 61131, type 3 | Yes |
| Input voltage | |
| • Rated value (DC) | 24 V |
| • for signal "0" | -30 to +5 V |
| • for signal "1" | +11 to +30V |
| Input current | |
| • for signal "1", typ. | 6.8 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | Yes; 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms (in each case + delay of 30 to 500 µs, depending on line length) |
| — at "0" to "1", min. | 0.05 ms |
| — at "0" to "1", max. | 20 ms |
| — at "1" to "0", min. | 0.05 ms |
| — at "1" to "0", max. | 20 ms |
| Cable length | |
| • shielded, max. | 1 000 m |
| • unshielded, max. | 600 m |
| Encoder | |
| Connectable encoders | |
| • 2-wire sensor | Yes |
| — permissible quiescent current (2-wire sensor), max. | 2 mA |
| Interrupts/diagnostics/status information | |
| Diagnostics function | Yes |
| Alarms | |
| • Diagnostic alarm | Yes |
| Diagnoses | |
| • Diagnostic information readable | Yes |
| • Monitoring the supply voltage | Yes |
| — parameterizable | Yes |
| • Monitoring of encoder power supply | No |
| • Wire-break | No |
| • Short-circuit | No |
| • Group error | Yes |
| Diagnostics indication LED | |
| • Monitoring of the supply voltage (PWR-LED) | Yes; green PWR LED |
| • Channel status display | Yes; green LED |
| • for channel diagnostics | No |
| • for module diagnostics | Yes; green/red DIAG LED |

| Potential separation | |
|--|---|
| Potential separation channels | |
| <ul style="list-style-type: none"> • between the channels | No |
| <ul style="list-style-type: none"> • between the channels and backplane bus | Yes |
| <ul style="list-style-type: none"> • between the channels and the power supply of the electronics | No |
| Isolation | |
| Isolation tested with | 707 V DC (type test) |
| Standards, approvals, certificates | |
| Suitable for safety functions | No |
| Ambient conditions | |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> • horizontal installation, min. | -30 °C; < 0 °C as of FS03 |
| <ul style="list-style-type: none"> • horizontal installation, max. | 60 °C |
| <ul style="list-style-type: none"> • vertical installation, min. | -30 °C; < 0 °C as of FS03 |
| <ul style="list-style-type: none"> • vertical installation, max. | 50 °C |
| Altitude during operation relating to sea level | |
| <ul style="list-style-type: none"> • Installation altitude above sea level, max. | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual |
| Dimensions | |
| Width | 15 mm |
| Height | 73 mm |
| Depth | 58 mm |
| Weights | |
| Weight, approx. | 28 g |
| last modified: | 9/24/2021  |