

SIMATIC DP, PROFIBUS DP Interface module IM 154-2 High Feature for ET 200 PRO incl. termination module, connection module in 6ES7194-4A.00-0AA0 order separately



General information	
Product type designation	IM 154-2 DP HF
Vendor identification (VendorID)	8119H
Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes; against destruction
Short-circuit protection	Yes; over exchangeable fuses
power supply according to NEC Class 2 required	No
Load voltage 2L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V
<ul style="list-style-type: none"> Reverse polarity protection 	Yes; against destruction
Input current	
from supply voltage 1L+, max.	200 mA
Power loss	
Power loss, typ.	5 W
Address area	
Addressing volume	
<ul style="list-style-type: none"> Inputs 	244 byte
<ul style="list-style-type: none"> Outputs 	244 byte
Interfaces	
Interfaces/bus type	PROFIBUS DP
Interface types	
RS 485	
<ul style="list-style-type: none"> Transmission rate, max. 	12 Mbit/s
<ul style="list-style-type: none"> automatic detection of transmission rate 	Yes
Protocols	
PROFIBUS DP	
Services	
<ul style="list-style-type: none"> — SYNC capability 	Yes
<ul style="list-style-type: none"> — FREEZE capability 	Yes
<ul style="list-style-type: none"> — Direct data exchange (slave-to-slave communication) 	Yes
Interrupts/diagnostics/status information	
Alarms	
<ul style="list-style-type: none"> Diagnostic alarm 	Yes; Parameterizable
<ul style="list-style-type: none"> Hardware interrupt 	Yes; Parameterizable
Diagnostics indication LED	
<ul style="list-style-type: none"> For load voltage monitoring 	Yes
<ul style="list-style-type: none"> Bus fault BF (red) 	Yes

<ul style="list-style-type: none"> • Group error SF (red) • Monitoring 24 V voltage supply ON (green) 	<p>Yes</p> <p>Yes</p>
Parameter	
DPV1 operation	possible
Swapping interrupt	Parameterizable
Startup if setpoint not equal to actual configuration	Parameterizable
Hot swapping of modules	possible
Potential separation	
between supply voltage and electronics	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Degree and class of protection	
IP degree of protection	IP65/67
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • min. • max. 	<p>-25 °C</p> <p>55 °C</p>
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> • min. • max. 	<p>-40 °C</p> <p>70 °C</p>
Dimensions	
Width	90 mm
Height	130 mm
Depth	60 mm
Weights	
Weight, approx.	375 g
last modified:	9/27/2021 