



SIMATIC ET 200SP, PROFINET interface module IM 155-6PN Basic, Max. 12 I/O modules, 2x integrated RJ45 sockets incl. server module

General information	
Product type designation	IM 155-6 PN BA
HW functional status	from FS04
Firmware version	
• FW update possible	Yes
Product function	
• I&M data	Yes; I&M0 to I&M3
• Module swapping during operation (hot swapping)	Yes; Single hot swapping
• Isochronous mode	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V13 SP1
• STEP 7 configurable/integrated from version	V5.5 SP4 and higher
• PROFINET from GSD version/GSD revision	V2.3 / -
Configuration control	
via dataset	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
Input current	
Current consumption, max.	300 mA
I ² t	0.09 A ² ·s
Power loss	
Power loss, typ.	1.8 W
Address area	
Address space per module	
• Address space per module, max.	32 byte; per input / output
Address space per station	
• Address space per station, max.	32 byte; per input / output
Hardware configuration	
Rack	
• Quantity of operable ET 200SP modules, max.	12
• Quantity of operable ET 200AL modules, max.	0
Interfaces	
Number of PROFINET interfaces	1; 2 ports (switch)

1. Interface

Interface types	
<ul style="list-style-type: none">• RJ 45 (Ethernet)	Yes; 2 integrated RJ45 ports
<ul style="list-style-type: none">• Number of ports	2
<ul style="list-style-type: none">• integrated switch	Yes
<ul style="list-style-type: none">• BusAdapter (PROFINET)	No
Protocols	
<ul style="list-style-type: none">• PROFINET IO Device	Yes
<ul style="list-style-type: none">• Open IE communication	Yes
<ul style="list-style-type: none">• Media redundancy	Yes; PROFINET MRP
Interface types	
RJ 45 (Ethernet)	
<ul style="list-style-type: none">• Transmission procedure	PROFINET with 100 Mbit/s full duplex (100BASE-TX)
<ul style="list-style-type: none">• 10 Mbps	No
<ul style="list-style-type: none">• 100 Mbps	Yes; PROFINET with 100 Mbit/s full duplex (100BASE-TX)
<ul style="list-style-type: none">• Autonegotiation	Yes
<ul style="list-style-type: none">• Autocrossing	Yes
Protocols	
PROFINET IO Device	
Services	
<ul style="list-style-type: none">— IRT	No
<ul style="list-style-type: none">— PROFIenergy	No
<ul style="list-style-type: none">— Prioritized startup	No
<ul style="list-style-type: none">— Shared device	No
Redundancy mode	
<ul style="list-style-type: none">• PROFINET system redundancy (S2)	No
Media redundancy	
<ul style="list-style-type: none">— MRP	Yes
<ul style="list-style-type: none">— MRPD	No
Open IE communication	
<ul style="list-style-type: none">• TCP/IP	Yes
<ul style="list-style-type: none">• SNMP	Yes
<ul style="list-style-type: none">• LLDP	Yes
Isochronous mode	
Equidistance	No
Interrupts/diagnostics/status information	
Status indicator	Yes
Alarms	Yes
Diagnostics function	Yes
Diagnostics indication LED	
<ul style="list-style-type: none">• RUN LED	Yes; green LED
<ul style="list-style-type: none">• ERROR LED	Yes; red LED
<ul style="list-style-type: none">• MAINT LED	Yes; Yellow LED
<ul style="list-style-type: none">• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
<ul style="list-style-type: none">• Connection display LINK TX/RX	Yes; 2x green link LEDs on BusAdapter
Potential separation	
between backplane bus and electronics	No
between PROFINET and all other circuits	Yes
between supply and all other circuits	No
Standards, approvals, certificates	
Network loading class	2
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none">• horizontal installation, min.	-30 °C
<ul style="list-style-type: none">• horizontal installation, max.	60 °C
<ul style="list-style-type: none">• vertical installation, min.	-30 °C
<ul style="list-style-type: none">• vertical installation, max.	50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none">• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual

connection method / header	
ET-Connection	
• via BU/BA Send	No
Dimensions	
Width	35 mm
Height	117 mm
Depth	74 mm
Weights	
Weight, approx.	125 g
last modified:	3/2/2021 