



SIMATIC DP, 5 electronic modules for ET 200S, 2 DI Standard 24 V DC, 15 mm width, 5 units per packing unit

Supply voltage		
Rated value (DC)	24 V; From power module	
Reverse polarity protection	Yes	
Input current		
from supply voltage L+, max.	Dependent on encoder	
from backplane bus 3.3 V DC, max.	10 mA	
Encoder supply		
Type of output voltage	min. L+ (-0.5 V), under load	
Output current		
<ul style="list-style-type: none"> <li>Rated value</li> <li>permissible range, lower limit</li> <li>permissible range, upper limit</li> </ul>	500 mA 0 mA 500 mA	
Power loss		
Power loss, typ.	0.4 W	
Address area		
Address space per module	<ul style="list-style-type: none"> <li>Address space per module, max.</li> <li>with packing</li> </ul>	1 byte 2 bit
Digital inputs		
Number of digital inputs	2	
Input characteristic curve in accordance with IEC 61131, type 1	Yes	
Input voltage		
<ul style="list-style-type: none"> <li>Type of input voltage</li> <li>Rated value (DC)</li> <li>for signal "0"</li> <li>for signal "1"</li> </ul>	DC 24 V -30 to +5 V +15 to +30 V	
Input current		
<ul style="list-style-type: none"> <li>for signal "1", typ.</li> </ul>	7 mA; at 24 V	
Input delay (for rated value of input voltage)		
for standard inputs	<ul style="list-style-type: none"> <li>parameterizable</li> <li>at "0" to "1", min.</li> <li>at "0" to "1", max.</li> <li>at "1" to "0", min.</li> <li>at "1" to "0", max.</li> </ul>	No 2 ms; typically 3 ms 4.5 ms 2 ms; typically 3 ms 4.5 ms
Cable length		
<ul style="list-style-type: none"> <li>shielded, max.</li> <li>unshielded, max.</li> </ul>	1 000 m 600 m	

Encoder	
Connectable encoders	
<ul style="list-style-type: none"> <li>• 2-wire sensor</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— permissible quiescent current (2-wire sensor), max.</li> </ul>	1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	No
Diagnostics indication LED	
<ul style="list-style-type: none"> <li>• Group error SF (red)</li> </ul>	No
<ul style="list-style-type: none"> <li>• Status indicator digital input (green)</li> </ul>	Yes; per channel
Parameter	
Remark	1 byte
Potential separation	
Potential separation digital inputs	
<ul style="list-style-type: none"> <li>• between the channels</li> </ul>	No
<ul style="list-style-type: none"> <li>• between the channels and backplane bus</li> </ul>	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	35 g
<b>last modified:</b>	2/9/2021 