SIEMENS

Data sheet

6ES7193-6BP20-0BB0



SIMATIC ET 200SP, BaseUnit BU20-P12+A4+0B, BU type B0, Push-in terminals, with 4 AUX terminals, bridged to the left, WxH: 20 mmx117 mm

General information		
Product type designation	BU type B0	
HW functional status	FS10 and higher	
Supply voltage		
Rated value (DC)	See manual	
For P1 and P2 bus	24 V	
 For AUX bus 	24 V; Equal potential group to P1/P2 bus or PE	
for process terminals	24 V	
Rated value (AC)	See manual	
For P1 and P2 bus	230 V	
 For AUX bus 	230 V; Equal potential group to P1/P2 bus or PE	
for process terminals	230 V	
Mains filter		
integrated	No	
Current carrying capacity		
up to 60 °C, max.	10 A	
For P1 and P2 bus, max.	10 A	
For AUX bus, max.	10 A	
For process terminals, max.	5 A	
Hardware configuration		
Automatic encoding	Yes	
Slots		
 Number of slots 	1	
Potential separation		
between backplane bus and supply voltage	Yes	
between process terminals and supply voltage	Yes	
between power bus and supply voltage	No	
Isolation		
Isolation tested with	3 100 V DC	
Ambient conditions		
Ambient temperature during operation		
horizontal installation, min.	-30 °C	
 horizontal installation, max. 	60 °C	
 vertical installation, min. 	-30 °C	
vertical installation, max.	50 °C	
Altitude during operation relating to sea level		
 Installation altitude above sea level, max. 	2 000 m; On request: Installation altitudes greater than 2 000 m	
Accessories		
Color coding labels		

 for AUX terminals 	CC81 to CC83	
connection method / header		
Terminals		
 Terminal type 	Push-in terminal	
 Conductor cross-section, min. 	0.14 mm²; AWG 26	
 Conductor cross-section, max. 	2.5 mm²; AWG 14	
 Number of process terminals to I/O module 	12; Pro slot	
 Number of terminals to AUX bus 	0	
 Number of add-on terminals 	0	
 Number of terminals with connection to P1 and P2 bus 	0; Pro slot	
Dimensions		
Width	20 mm	
Height	117 mm	
Depth	35 mm	
Weights		
Weight, approx.	48 g	
last modified:	2/7/2021 🗗	