



\*\*\* spare part \*\*\* SIMATIC S7-200, digital input EM 221, isolated 8 DI, 120/230 V AC

Input current	
from backplane bus 5 V DC, max.	30 mA
Power loss	
Power loss, typ.	3 W
Digital inputs	
Number of digital inputs	8
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input voltage	
<ul style="list-style-type: none"> <li>Type of input voltage</li> <li>Rated value (AC)</li> <li>for signal "0"</li> <li>for signal "1"</li> </ul>	AC 230 V; 220/230 V AC (47 Hz to 63 Hz) up to 20 V AC 79V AC or more
Input current	
<ul style="list-style-type: none"> <li>for signal "1", typ.</li> </ul>	2.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	15 ms
Cable length	
<ul style="list-style-type: none"> <li>shielded, max.</li> <li>unshielded, max.</li> </ul>	500 m 300 m
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> <li>2-wire sensor</li> <li>— permissible quiescent current (2-wire sensor), max.</li> </ul>	Yes 1 mA
Potential separation	
Potential separation digital inputs	
<ul style="list-style-type: none"> <li>Potential separation digital inputs</li> <li>between the channels, in groups of</li> </ul>	Yes; Optocoupler 1; 8 groups
connection method / header	
Plug-in I/O terminals	Yes
Dimensions	
Width	71.2 mm
Height	80 mm
Depth	62 mm
Weights	
Weight, approx.	160 g
last modified:	3/12/2021

