



SIMATIC S7-300, CPU 317T-3 PN/DP, Central processing unit for PLC and technology tasks, 1024 KB work memory, 1st interface MPI/DP 12 Mbit/s, 2nd interface DP (drive), 3rd interface Ethernet PROFINET with 2-port switch, Integr. I/O for technology, Front connector (1x 40-pole) and Micro Memory Card min. 8 MB required

General information	
HW functional status	01
Firmware version	CPU: V3.2; integrated technology V4.1.5
Product function	
<ul style="list-style-type: none"> • Isochronous mode 	Yes; Via PROFIBUS DP or PROFINET interface
Engineering with	
<ul style="list-style-type: none"> • Programming package 	STEP 7 V5.5 SP2 or higher and S7-Technology option package V4.2 SP3
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2 A min.
Load voltage L+	
<ul style="list-style-type: none"> • Rated value (DC) • Reverse polarity protection 	24 V Yes
Digital outputs	
— Rated value (DC)	24 V; 2L+
— Reverse polarity protection	No; 2L+
Input current	
Current consumption (rated value)	1 050 mA
Current consumption (in no-load operation), typ.	230 mA
Inrush current, typ.	6.5 A
I^2t	1 A ² ·s
Power loss	
Power loss, typ.	7.5 W
Memory	
Work memory	
<ul style="list-style-type: none"> • integrated • expandable 	1 024 kbyte No
Load memory	
<ul style="list-style-type: none"> • Plug-in (MMC) • Plug-in (MMC), max. • Data management on MMC (after last programming), min. 	Yes 8 Mbyte 10 y
Backup	
<ul style="list-style-type: none"> • present • without battery 	Yes; Guaranteed by MMC (maintenance-free) Yes; Program and data

CPU processing times	
for bit operations, typ.	0.025 µs
for word operations, typ.	0.03 µs
for fixed point arithmetic, typ.	0.04 µs
for floating point arithmetic, typ.	0.16 µs
CPU-blocks	
Number of blocks (total)	2 048; (DBs, FCs, FBs); the maximum number of loadable blocks can be reduced by the MMC used.
DB	
<ul style="list-style-type: none"> Number, max. Size, max. 	2 048; Number range: 1 to 16000 64 kbyte
FB	
<ul style="list-style-type: none"> Number, max. Size, max. 	2 048; Number range: 0 to 7999 64 kbyte
FC	
<ul style="list-style-type: none"> Number, max. Size, max. 	2 048; Number range: 0 to 7999 64 kbyte
OB	
<ul style="list-style-type: none"> Number, max. Size, max. Number of free cycle OBs Number of time alarm OBs Number of delay alarm OBs Number of cyclic interrupt OBs Number of process alarm OBs Number of DPV1 alarm OBs Number of isochronous mode OBs Number of technology synchronous alarm OBs Number of startup OBs Number of asynchronous error OBs Number of synchronous error OBs 	see instruction list 64 kbyte 1; OB 1 1; OB 10 2; OB 20, 21 4; OB 32, 33, 34, 35 1; OB 40 3; OB 55, 56, 57 1; OB 61 - isochronous mode is possible either on DP or PROFINET IO (not simultaneously) 1; OB 65 1; OB 100 6; OB 80, 82, 83, 85, 86, 87 (OB83 only for PROFINET IO) 2; OB 121, 122
Nesting depth	
<ul style="list-style-type: none"> per priority class additional within an error OB 	16 4
Counters, timers and their retentivity	
S7 counter	
<ul style="list-style-type: none"> Number 	512
Retentivity	
<ul style="list-style-type: none"> adjustable lower limit upper limit preset 	Yes 0 511 Z 0 to Z 7
Counting range	
<ul style="list-style-type: none"> adjustable lower limit upper limit 	Yes 0 999
IEC counter	
<ul style="list-style-type: none"> present Type Number 	Yes SFB Unlimited (limited only by RAM capacity)
S7 times	
<ul style="list-style-type: none"> Number 	512
Retentivity	
<ul style="list-style-type: none"> adjustable lower limit upper limit preset 	Yes 0 511 No retentivity
Time range	
<ul style="list-style-type: none"> lower limit 	10 ms

— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	256 kbyte
Flag	
• Size, max.	4 096 byte
• Retentivity available	Yes; From MB 0 to MB 4 095
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
Data blocks	
• Retentivity adjustable	Yes; via non-retain property on DB
• Retentivity preset	Yes
Local data	
• per priority class, max.	32 768 byte; Max. 2048 bytes per block
Address area	
I/O address area	
• Inputs	8 192 byte
• Outputs	8 192 byte
of which distributed	
— Inputs	8 192 byte
— Outputs	8 192 byte
Process image	
• Inputs	8 192 byte
• Outputs	8 192 byte
• Inputs, adjustable	8 192 byte
• Outputs, adjustable	8 192 byte
• Inputs, default	256 byte
• Outputs, default	256 byte
Default addresses of the integrated channels	
— Digital inputs	66
— Digital outputs	66
Subprocess images	
• Number of subprocess images, max.	1; With PROFINET IO, the length of the user data is limited to 1600 bytes
Digital channels	
• Inputs	65 536
— of which central	256
• Outputs	65 536
— of which central	256
Analog channels	
• Inputs	4 096
— of which central	64
• Outputs	4 096
— of which central	64
Hardware configuration	
Number of expansion units, max.	0
Number of DP masters	
• integrated	2; 1 DP and 1 DP (drive)
• via CP	2; for DP
Number of operable FMs and CPs (recommended)	
• FM	8
• CP, PtP	8
• CP, LAN	8
Rack	
• Racks, max.	1
• Modules per rack, max.	8
Time of day	

Clock	
<ul style="list-style-type: none"> • Hardware clock (real-time) • retentive and synchronizable • Backup time • Deviation per day, max. • Behavior of the clock following POWER-ON • Behavior of the clock following expiry of backup period 	<p>Yes</p> <p>Yes</p> <p>6 wk; At 40 °C ambient temperature</p> <p>10 s; Typ.: 2 s</p> <p>Clock continues running after POWER OFF</p> <p>the clock continues at the time of day it had when power was switched off</p>
Operating hours counter	
<ul style="list-style-type: none"> • Number • Number/Number range • Range of values • Granularity • retentive 	<p>4</p> <p>0 to 3</p> <p>0 to 2³¹ hours (when using SFC 101)</p> <p>1 h</p> <p>Yes; Must be restarted at each restart</p>
Clock synchronization	
<ul style="list-style-type: none"> • supported • to MPI, master • to MPI, slave • to DP, master • to DP, slave • in AS, master • in AS, slave • on Ethernet via NTP 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes; Only time-of-day slave</p> <p>Yes</p> <p>Yes</p> <p>Yes; As client</p>
Digital inputs	
Number of digital inputs	4
<ul style="list-style-type: none"> • of which inputs usable for technological functions 	4
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
horizontal installation	
— up to 40 °C, max.	4
— up to 60 °C, max.	4
vertical installation	
— up to 40 °C, max.	4
Input voltage	
<ul style="list-style-type: none"> • Rated value (DC) • for signal "0" • for signal "1" 	<p>24 V</p> <p>-3 to +5V</p> <p>+15 to +30 V</p>
Input current	
<ul style="list-style-type: none"> • for signal "1", typ. 	7 mA
Input delay (for rated value of input voltage)	
for technological functions	
— at "0" to "1", max.	10 µs; Typical
— at "1" to "0", max.	10 µs; Typical
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	1 000 m
Digital outputs	
Number of digital outputs	8
<ul style="list-style-type: none"> • of which high-speed outputs 	8
Functions	for technology functions, e.g. high-speed cam switch signals
Short-circuit protection	Yes
<ul style="list-style-type: none"> • Response threshold, typ. 	1 A
Limitation of inductive shutdown voltage to	48 V
Controlling a digital input	No
Switching capacity of the outputs	
<ul style="list-style-type: none"> • on lamp load, max. 	5 W
Load resistance range	
<ul style="list-style-type: none"> • lower limit • upper limit 	<p>48 Ω</p> <p>4 kΩ</p>
Output voltage	

<ul style="list-style-type: none"> • for signal "0", max. • for signal "1", min. 	3 V; (2L+) Rated voltage -2.5 V
Output current	
<ul style="list-style-type: none"> • for signal "1" rated value • for signal "1" permissible range for 0 to 60 °C, min. • for signal "1" permissible range for 0 to 60 °C, max. • for signal "0" residual current, max. 	0.5 A 5 mA 0.6 A 0.3 mA
Parallel switching of two outputs	
<ul style="list-style-type: none"> • for uprating • for redundant control of a load 	No No
Switching frequency	
<ul style="list-style-type: none"> • with resistive load, max. • with inductive load, max. • on lamp load, max. 	100 Hz 0.2 Hz; According to IEC 60947-5-1, DC-13 100 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 40 °C, max.	4 A
— up to 60 °C, max.	3 A
all other mounting positions	
— up to 40 °C, max.	4 A
Integrated high-speed cams	
<ul style="list-style-type: none"> • Switching accuracy (+/-) 	70 µs
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	1 000 m
Analog inputs	
Number of analog inputs	0
Analog outputs	
Number of analog outputs	0
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> • 2-wire sensor 	No
Interfaces	
Number of industrial Ethernet interfaces	1
Number of PROFINET interfaces	1
Number of RS 485 interfaces	2
Number of RS 422 interfaces	0
1. Interface	
Interface type	Integrated RS 485 interface
Isolated	Yes
Interface types	
<ul style="list-style-type: none"> • RS 485 • Output current of the interface, max. 	Yes 200 mA
Protocols	
<ul style="list-style-type: none"> • MPI • PROFIBUS DP master • PROFIBUS DP slave • Point-to-point connection 	Yes Yes Yes No
MPI	
<ul style="list-style-type: none"> • Transmission rate, max. 	12 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	No; but via CP and loadable FB
— S7 communication, as server	Yes
PROFINET DP master	
<ul style="list-style-type: none"> • Transmission rate, max. 	12 Mbit/s

• Number of DP slaves, max.	124
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	Yes; I blocks only
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes
— Equidistance	Yes
— Isochronous mode	Yes; OB 61; isochronous mode can only be used alternatively on PROFIBUS DP or PROFINET IO
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Number of DP slaves that can be simultaneously activated/deactivated, max.	8
— Direct data exchange (slave-to-slave communication)	Yes; as subscriber
— DPV1	Yes
Address area	
— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
PROFIBUS DP slave	
• Transmission rate, max.	12 Mbit/s
• automatic baud rate search	Yes; only with passive interface
• Address area, max.	32
• User data per address area, max.	32 byte
Services	
— PG/OP communication	Yes
— Routing	Yes; Only with active interface
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes; Connection configured on one side only
— Direct data exchange (slave-to-slave communication)	Yes
— DPV1	No
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte
2. Interface	
Interface type	Integrated RS 485 interface
Isolated	Yes
Interface types	
• RS 485	Yes
• Output current of the interface, max.	200 mA
Protocols	
• MPI	No
• PROFIBUS DP master	Yes; DP(DRIVE)-Master
• PROFIBUS DP slave	No
• Point-to-point connection	No
PROFIBUS DP master	
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	64
Services	
— PG/OP communication	No
— Routing	No

— Global data communication	No
— S7 basic communication	No
— S7 communication	No
— Equidistance	Yes
— Isochronous mode	Yes
— SYNC/FREEZE	No
— Activation/deactivation of DP slaves	Yes
— DPV1	No
Address area	
— Inputs, max.	1 024 byte
— Outputs, max.	1 024 byte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
PROFIBUS DP slave	
• GSD file	http://support.automation.siemens.com in Product Support area
• Transmission rate, max.	12 Mbit/s
3. Interface	
Interface type	PROFINET
Isolated	Yes
automatic detection of transmission rate	Yes; 10/100 Mbit/s
Autonegotiation	Yes
Autocrossing	Yes
Change of IP address at runtime, supported	Yes
Interface types	
• RJ 45 (Ethernet)	Yes
• Number of ports	2
• integrated switch	Yes
Protocols	
• MPI	No
• PROFINET IO Controller	Yes; Also simultaneously with IO-Device functionality
• PROFINET IO Device	Yes; Also simultaneously with IO Controller functionality
• PROFIBUS DP master	No
• PROFIBUS DP slave	No
• Open IE communication	Yes; Via TCP/IP, ISO on TCP, and UDP
• Web server	Yes
• Media redundancy	Yes
PROFINET IO Controller	
• Transmission rate, max.	100 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— S7 communication	Yes; with loadable FBs, max. configurable connections: 16, max. number of instances: 32
— Isochronous mode	Yes; OB 61; isochronous mode can only be used alternatively on PROFIBUS DP or PROFINET IO
— Shared device	Yes
— Prioritized startup	Yes
— Number of IO devices with prioritized startup, max.	32
— Number of connectable IO Devices, max.	128
— Of which IO devices with IRT, max.	64
— of which in line, max.	64
— Number of connectable IO Devices for RT, max.	128
— of which in line, max.	128
— Activation/deactivation of IO Devices	Yes
— Number of IO Devices that can be simultaneously activated/deactivated, max.	8
— IO Devices changing during operation (partner ports), supported	Yes

— Number of IO Devices per tool, max.	8
— Device replacement without swap medium	Yes
— Send cycles	250 µs, 500 µs, 1 ms, 2 ms, 4 ms
— Updating time	250 µs to 512 ms (depending on the operating mode, see Manual "S7-300 CPU 31xC and CPU 31x, technical Data" for more details)
Address area	
— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte
— User data consistency, max.	1 024 byte
PROFINET IO Device	
Services	
— PG/OP communication	Yes
— Routing	Yes
— S7 communication	Yes; with loadable FBs, max. configurable connections: 16, max. number of instances: 32
— Isochronous mode	No
— IRT	Yes
— PROFlenergy	Yes; With SFB 73 / 74 prepared for loadable PROFlenergy standard FB for I-Device
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2
Transfer memory	
— Inputs, max.	1 440 byte; Per IO Controller with shared device
— Outputs, max.	1 440 byte; Per IO Controller with shared device
Submodules	
— Number, max.	64
— User data per submodule, max.	1 024 byte
Open IE communication	
• Number of connections, max.	16
• Local port numbers used at the system end	0, 20, 21, 23, 25, 80, 102, 135, 161, 443, 8080, 34962, 34963, 34964, 65532, 65533, 65534, 65535
• Keep-alive function, supported	Yes
Protocols	
PROFIsafe	No
Redundancy mode	
Media redundancy	
— Switchover time on line break, typ.	200 ms; PROFINET MRP
— Number of stations in the ring, max.	50
Open IE communication	
• TCP/IP	Yes; via integrated PROFINET interface and loadable FBs
— Number of connections, max.	16
— Data length for connection type 01H, max.	1 460 byte
— Data length for connection type 11H, max.	32 768 byte
— several passive connections per port, supported	Yes
• ISO-on-TCP (RFC1006)	Yes; via integrated PROFINET interface and loadable FBs
— Number of connections, max.	16
— Data length, max.	32 768 byte
• UDP	Yes; via integrated PROFINET interface and loadable FBs
— Number of connections, max.	16
— Data length, max.	1 472 byte
Web server	
• supported	Yes
• User-defined websites	Yes
• Number of HTTP clients	5
communication functions / header	
PG/OP communication	Yes
Data record routing	Yes
Global data communication	
• supported	Yes

• Number of GD loops, max.	8
• Number of GD packets, max.	8
• Number of GD packets, transmitter, max.	8
• Number of GD packets, receiver, max.	8
• Size of GD packets, max.	22 byte
• Size of GD packet (of which consistent), max.	22 byte
S7 basic communication	
• supported	Yes
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes; via integrated PROFINET interface and loadable FB or via CP and loadable FB
• User data per job, max.	See online help of STEP 7 (shared parameters of the SFBs/FBs and of the SFCs/FCs of S7 Communication)
S5 compatible communication	
• supported	Yes; via CP and loadable FC
Number of connections	
• overall	32
• usable for PG communication	31
— reserved for PG communication	1
— adjustable for PG communication, min.	1
— adjustable for PG communication, max.	31
• usable for OP communication	31
— reserved for OP communication	1
— adjustable for OP communication, min.	1
— adjustable for OP communication, max.	31
• usable for S7 basic communication	30
— reserved for S7 basic communication	0
— adjustable for S7 basic communication, min.	0
— adjustable for S7 basic communication, max.	30
• usable for S7 communication	16
— reserved for S7 communication	0
— adjustable for S7 communication, min.	0
— adjustable for S7 communication, max.	16
• total number of instances, max.	32
• usable for routing	X1 as MPI: max. 10; X1 as DP master: max. 24; X1 as DP slave (active): max. 14; X2 as PROFINET: 24 max.
S7 message functions	
Number of login stations for message functions, max.	32; Depending on the configured connections for PG/OP and S7 basic communication
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	300
Test commissioning functions	
Status block	Yes; Up to 2 simultaneously
Single step	Yes
Number of breakpoints	4; without continuation
Status/control	
• Status/control variable	Yes
• Variables	Inputs, outputs, memory bits, DB, times, counters
• Number of variables, max.	30
— of which status variables, max.	30
— of which control variables, max.	14
Forcing	
• Forcing	Yes
• Forcing, variables	Inputs, outputs
• Number of variables, max.	10
Diagnostic buffer	

<ul style="list-style-type: none"> • present 	Yes
<ul style="list-style-type: none"> • Number of entries, max. <ul style="list-style-type: none"> — adjustable — of which powerfail-proof 	500 No 100; Only the last 100 entries are retained
<ul style="list-style-type: none"> • Number of entries readable in RUN, max. <ul style="list-style-type: none"> — adjustable — preset 	499 Yes; From 10 to 499 10
Service data	
<ul style="list-style-type: none"> • can be read out 	Yes
Interrupts/diagnostics/status information	
Alarms	No
Diagnostics function	No
Diagnostics indication LED	
<ul style="list-style-type: none"> • Status indicator digital input (green) • Status indicator digital output (green) 	Yes Yes
Potential separation	
Potential separation digital inputs	
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes
Potential separation digital outputs	
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes
Isolation	
Isolation tested with	500 V DC
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • min. • max. 	0 °C 60 °C
configuration / header	
Configuration software	
<ul style="list-style-type: none"> • STEP 7 	Yes; STEP 7 V5.5 SP2 or higher and S7-Technology option package V4.2 SP3
configuration / programming / header	
<ul style="list-style-type: none"> • Command set • Nesting levels • System functions (SFC) • System function blocks (SFB) 	see instruction list 8 see instruction list see instruction list
Programming language	
<ul style="list-style-type: none"> — LAD — FBD — STL — SCL — CFC — GRAPH — HiGraph® 	Yes Yes Yes Yes Yes Yes Yes
Know-how protection	
<ul style="list-style-type: none"> • User program protection/password protection • Block encryption 	Yes Yes; With S7 block Privacy
Dimensions	
Width	120 mm
Height	125 mm
Depth	130 mm
Weights	
Weight, approx.	640 g
last modified:	8/24/2021 