



Figure similar

SIMATIC S7-300, Analog module SM 334, Non-isolated 4 AI/2 AO, 1x 20-pole, Removing and inserting possible with active backplane bus

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
Input current	
from supply and load voltage L+ (without load), max.	110 mA
from backplane bus 5 V DC, max.	55 mA
Power loss	
Power loss, typ.	3 W
Analog inputs	
Number of analog inputs	4
• For voltage measurement	4
permissible input voltage for voltage input (destruction limit), max.	20 V
permissible input current for current input (destruction limit), max.	40 mA
Cycle time (all channels) max.	5 ms
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
Input ranges (rated values), voltages	
• 0 to +10 V	Yes
— Input resistance (0 to 10 V)	100 kΩ
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	50 Ω
Cable length	
• shielded, max.	200 m
Analog outputs	
Number of analog outputs	2
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	11 mA
Current output, no-load voltage, max.	15 V
Output ranges, voltage	
• 0 to 10 V	Yes
Output ranges, current	

• 0 to 20 mA	Yes
<b>Load impedance (in rated range of output)</b>	
• with voltage outputs, min.	5 k $\Omega$
• with voltage outputs, capacitive load, max.	1 $\mu$ F
• with current outputs, max.	300 $\Omega$
• with current outputs, inductive load, max.	1 mH
<b>Cable length</b>	
• shielded, max.	200 m
<b>Analog value generation for the inputs</b>	
<b>Integration and conversion time/resolution per channel</b>	
• Resolution with overrange (bit including sign), max.	8 bit
• Integration time, parameterizable	No
<b>Analog value generation for the outputs</b>	
<b>Integration and conversion time/resolution per channel</b>	
• Resolution with overrange (bit including sign), max.	8 bit
• Conversion time (per channel)	500 $\mu$ s
<b>Settling time</b>	
• for resistive load	0.3 ms
• for capacitive load	3 ms
• for inductive load	0.3 ms
<b>Encoder</b>	
<b>Connection of signal encoders</b>	
• for voltage measurement	Yes
• for current measurement as 2-wire transducer	No
• for current measurement as 4-wire transducer	Yes
<b>Errors/accuracies</b>	
<b>Operational error limit in overall temperature range</b>	
• Voltage, relative to input range, (+/-)	0.9 %
• Current, relative to input range, (+/-)	0.8 %
• Voltage, relative to output range, (+/-)	0.6 %
• Current, relative to output range, (+/-)	1 %
<b>Basic error limit (operational limit at 25 °C)</b>	
• Voltage, relative to input range, (+/-)	0.7 %
• Current, relative to input range, (+/-)	0.6 %
• Voltage, relative to output range, (+/-)	0.5 %
• Current, relative to output range, (+/-)	0.5 %
<b>Interrupts/diagnostics/status information</b>	
Alarms	No
Diagnostics function	No
<b>Potential separation</b>	
<b>Potential separation analog inputs</b>	
• between the channels and backplane bus	No
<b>Potential separation analog outputs</b>	
• between the channels	No
• between the channels and backplane bus	No
• between the channels and the power supply of the electronics	Yes
<b>Isolation</b>	
Isolation tested with	500 V DC
<b>connection method / header</b>	
required front connector	20-pin
<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	117 mm
<b>Weights</b>	
Weight, approx.	285 g

**last modified:** 1/17/2021 

