



Figure similar

SIMATIC S7-300, positioning module FM 351 for rapid/slow traverse Drives incl. configuration package on CD

Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>permissible range, lower limit (DC)</li> </ul>	20.4 V
<ul style="list-style-type: none"> <li>permissible range, upper limit (DC)</li> </ul>	28.8 V
Input current	
Current consumption, max.	350 mA
from backplane bus 5 V DC, max.	150 mA
Encoder supply	
5 V encoder supply	
<ul style="list-style-type: none"> <li>5 V</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Output current, max.</li> </ul>	350 mA
<ul style="list-style-type: none"> <li>Cable length, max.</li> </ul>	32 m
24 V encoder supply	
<ul style="list-style-type: none"> <li>24 V</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Output current, max.</li> </ul>	400 mA; Per channel
<ul style="list-style-type: none"> <li>Cable length, max.</li> </ul>	100 m
Power loss	
Power loss, typ.	7.9 W
Digital inputs	
Number of digital inputs	8
Functions	Reference cams, reversing cams, flying actual value setting, start/stop positioning
Input voltage	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>for signal "0"</li> </ul>	-3 to +5V
<ul style="list-style-type: none"> <li>for signal "1"</li> </ul>	+11 to +30V
Input current	
<ul style="list-style-type: none"> <li>for signal "0", max. (permissible quiescent current)</li> </ul>	2 mA
<ul style="list-style-type: none"> <li>for signal "1", typ.</li> </ul>	6 mA
Digital outputs	
Number of digital outputs	8
Functions	Rapid traverse, creep, run right, run left
Short-circuit protection	Yes
Output voltage	

<ul style="list-style-type: none"> <li>Rated value (DC)</li> <li>for signal "1", min.</li> </ul>	24 V UP - 0.8 V
<b>Output current</b>	
<ul style="list-style-type: none"> <li>for signal "1" permissible range for 0 to 60 °C, min.</li> <li>for signal "1" permissible range for 0 to 60 °C, max.</li> <li>for signal "0" residual current, max.</li> </ul>	5 mA; with UPmax 600 mA; with UPmax 0.5 mA
<b>Encoder</b>	
<b>Connectable encoders</b>	
<ul style="list-style-type: none"> <li>Incremental encoder (symmetrical)</li> <li>Incremental encoder (asymmetrical)</li> <li>Absolute encoder (SSI)</li> <li>2-wire sensor               <ul style="list-style-type: none"> <li>permissible quiescent current (2-wire sensor), max.</li> </ul> </li> </ul>	Yes Yes Yes Yes 2 mA; on signal "0", max. 2 mA; on signal "1", max. 6 mA
<b>Encoder signals, incremental encoder (symmetrical)</b>	
<ul style="list-style-type: none"> <li>Trace mark signals</li> <li>Zero mark signal</li> <li>Input voltage</li> <li>Input frequency, max.</li> </ul>	A, notA, B, notB N, notN 5 V difference signal (phys. RS 422) 0.5 MHz
<b>Encoder signals, incremental encoder (asymmetrical)</b>	
<ul style="list-style-type: none"> <li>Trace mark signals</li> <li>Zero mark signal</li> <li>Input voltage</li> <li>Input frequency, max.</li> </ul>	A, B N 24 V 50 kHz; 50 kHz for 25 m cable length; 25 kHz for 100 m cable length
<b>Encoder signals, absolute encoder (SSI)</b>	
<ul style="list-style-type: none"> <li>Input signal</li> <li>Data signal</li> <li>Clock signal</li> <li>Telegram length, parameterizable</li> <li>Clock frequency, max.</li> <li>Gray code</li> <li>Cable length, shielded, max.</li> </ul>	5 V difference signal (phys. RS 422) DATA, notDATA CL, notCL 13 or 25 bit 1.5 MHz Yes 200 m; At max. 188 kHz
<b>Potential separation</b>	
<b>Potential separation digital inputs</b>	
<ul style="list-style-type: none"> <li>Potential separation digital inputs</li> </ul>	Yes
<b>Potential separation digital outputs</b>	
<ul style="list-style-type: none"> <li>Potential separation digital outputs</li> </ul>	Yes
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>	0 °C 60 °C
<b>Ambient temperature during storage/transportation</b>	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>	-40 °C 70 °C
<b>connection method / header</b>	
required front connector	1x 20-pin
<b>Dimensions</b>	
Width	80 mm
Height	125 mm
Depth	120 mm
<b>Weights</b>	
Weight, approx.	550 g
<b>last modified:</b>	1/16/2021 