



Figure similar

SIMATIC S7-300, Control Unit FM 355 S, 4 channels, Step and pulse, 4 AI+8 DI+8 DO incl. multi-language configuration package, Manual and Getting Started (de, de, fr, en fr, it) on CD-ROM

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>permissible range, lower limit (DC)</li> </ul>	20.4 V
<ul style="list-style-type: none"> <li>permissible range, upper limit (DC)</li> </ul>	28.8 V
Input current	
from load voltage L+ (without load), max.	270 mA; typ. 220 mA
from backplane bus 5 V DC, max.	75 mA; typ. 50 mA
Power loss	
Power loss, typ.	5.5 W
Power loss, max.	6.9 W
Digital inputs	
Number of digital inputs	8
Input characteristic curve in accordance with IEC 61131, type 2	Yes
Input voltage	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>for signal "0"</li> </ul>	-3 to +5V
<ul style="list-style-type: none"> <li>for signal "1"</li> </ul>	13 to 30V
Input current	
<ul style="list-style-type: none"> <li>for signal "1", typ.</li> </ul>	7 mA
Cable length	
<ul style="list-style-type: none"> <li>shielded, max.</li> </ul>	1 000 m
<ul style="list-style-type: none"> <li>unshielded, max.</li> </ul>	600 m
Digital outputs	
Number of digital outputs	8
Short-circuit protection	Yes; Electronic
Limitation of inductive shutdown voltage to	L+ (-1.5 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	5 W
Load resistance range	
<ul style="list-style-type: none"> <li>lower limit</li> </ul>	240 Ω
<ul style="list-style-type: none"> <li>upper limit</li> </ul>	4 kΩ
Output voltage	
<ul style="list-style-type: none"> <li>for signal "1", min.</li> </ul>	L+ (-2.5 V)
Output current	
<ul style="list-style-type: none"> <li>for signal "1" rated value</li> </ul>	100 mA

<ul style="list-style-type: none"> <li>• for signal "1" permissible range for 0 to 60 °C, min.</li> <li>• for signal "1" permissible range for 0 to 60 °C, max.</li> <li>• for signal "0" residual current, max.</li> </ul>	5 mA 150 mA 0.5 mA
<b>Parallel switching of two outputs</b>	
<ul style="list-style-type: none"> <li>• for logic links</li> </ul>	Yes
<b>Switching frequency</b>	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> <li>• with inductive load, max.</li> <li>• on lamp load, max.</li> </ul>	100 Hz 0.5 Hz 100 Hz
<b>Total current of the outputs (per group)</b>	
all mounting positions	
— up to 60 °C, max.	400 mA
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> <li>• unshielded, max.</li> </ul>	1 000 m 600 m
<b>Analog inputs</b>	
Number of analog inputs	4
permissible input voltage for voltage input (destruction limit), max.	30 V
permissible input current for current input (destruction limit), max.	40 mA
<b>Input ranges</b>	
<ul style="list-style-type: none"> <li>• Voltage</li> <li>• Current</li> <li>• Thermocouple</li> <li>• Resistance thermometer</li> </ul>	Yes Yes Yes Yes
<b>Input ranges (rated values), voltages</b>	
<ul style="list-style-type: none"> <li>• 0 to +10 V               <ul style="list-style-type: none"> <li>— Input resistance (0 to 10 V)</li> </ul> </li> <li>• -1.75 V to +11.75 V               <ul style="list-style-type: none"> <li>— Input resistance (-1.75 V to +11.75 V)</li> </ul> </li> <li>• -80 mV to +80 mV               <ul style="list-style-type: none"> <li>— Input resistance (-80 mV to +80 mV)</li> </ul> </li> </ul>	Yes 100 kΩ Yes 100 kΩ Yes 10 MΩ
<b>Input ranges (rated values), currents</b>	
<ul style="list-style-type: none"> <li>• 0 to 20 mA               <ul style="list-style-type: none"> <li>— Input resistance (0 to 20 mA)</li> </ul> </li> <li>• 0 to 23.5 mA               <ul style="list-style-type: none"> <li>— Input resistance (0 to 23.5 mA)</li> </ul> </li> <li>• -3.5 mA to +23.5 mA               <ul style="list-style-type: none"> <li>— Input resistance (-3.5 mA to +23.5 mA)</li> </ul> </li> <li>• 4 mA to 20 mA               <ul style="list-style-type: none"> <li>— Input resistance (4 mA to 20 mA)</li> </ul> </li> </ul>	Yes 50 Ω Yes 50 Ω Yes 50 Ω Yes 50 Ω
<b>Input ranges (rated values), thermocouples</b>	
<ul style="list-style-type: none"> <li>• Type B               <ul style="list-style-type: none"> <li>— Input resistance (Type B)</li> </ul> </li> <li>• Type J               <ul style="list-style-type: none"> <li>— Input resistance (type J)</li> </ul> </li> <li>• Type K               <ul style="list-style-type: none"> <li>— Input resistance (Type K)</li> </ul> </li> <li>• Type R               <ul style="list-style-type: none"> <li>— Input resistance (Type R)</li> </ul> </li> <li>• Type S               <ul style="list-style-type: none"> <li>— Input resistance (Type S)</li> </ul> </li> </ul>	Yes 10 MΩ Yes 10 MΩ Yes 10 MΩ Yes 10 MΩ Yes 10 MΩ
<b>Input ranges (rated values), resistance thermometer</b>	
<ul style="list-style-type: none"> <li>• Pt 100               <ul style="list-style-type: none"> <li>— Input resistance (Pt 100)</li> </ul> </li> </ul>	Yes 10 MΩ
<b>Thermocouple (TC)</b>	
Temperature compensation	
<ul style="list-style-type: none"> <li>— internal temperature compensation</li> <li>— external temperature compensation with Pt100</li> </ul>	Yes Yes

<b>Characteristic linearization</b>	
<ul style="list-style-type: none"> <li>parameterizable <ul style="list-style-type: none"> <li>for thermocouples</li> <li>for resistance thermometer</li> </ul> </li> </ul>	Yes Type B, J, K, R, S Pt100 (standard)
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>shielded, max.</li> </ul>	200 m; 50 m at 80 mV and thermocouples
<b>Analog value generation for the inputs</b>	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> <li>Resolution with overrange (bit including sign), max.</li> </ul>	14 bit; 12 bit or 14 bit, parameterizable
<b>Encoder</b>	
Connection of signal encoders	
<ul style="list-style-type: none"> <li>for voltage measurement</li> <li>for current measurement as 4-wire transducer</li> </ul>	Yes Yes
Connectable encoders	
<ul style="list-style-type: none"> <li>2-wire sensor <ul style="list-style-type: none"> <li>permissible quiescent current (2-wire sensor), max.</li> </ul> </li> </ul>	Yes 1.5 mA
<b>Errors/accuracies</b>	
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> <li>Voltage, relative to input range, (+/-)</li> <li>Current, relative to input range, (+/-)</li> <li>Resistance thermometer, relative to input range, (+/-)</li> </ul>	0.6 %; $\pm 0.6$ to $\pm 1\%$ 0.6 %; $\pm 0.6$ to $\pm 1\%$ 0.6 %; $\pm 0.6$ to $\pm 1\%$
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> <li>Voltage, relative to input range, (+/-)</li> <li>Current, relative to input range, (+/-)</li> <li>Resistance thermometer, relative to input range, (+/-)</li> </ul>	0.4 %; 80 mV: $\pm 0.6\%$ ; 250 to 1 000 mV: $\pm 0.4\%$ ; 2.5 to 10 V: $\pm 0.6\%$ ; 3.2 to 20 mA: $\pm 0.5\%$ 0.4 %; $\pm 0.4$ to $\pm 0.6\%$ 0.4 %; $\pm 0.4$ to $\pm 0.6\%$
<b>Interrupts/diagnostics/status information</b>	
Substitute values connectable	Yes; Parameterizable
<b>Integrated Functions</b>	
Counter	No
Control technology	
<ul style="list-style-type: none"> <li>Number of closed-loop controllers</li> </ul>	4
<b>Potential separation</b>	
Potential separation controller	
<ul style="list-style-type: none"> <li>between the channels</li> <li>between the channels and backplane bus</li> </ul>	No Yes; Optocoupler
<b>Isolation</b>	
Isolation tested with	500 V DC
<b>connection method / header</b>	
required front connector	2x 20-pin
<b>Dimensions</b>	
Width	80 mm
Height	125 mm
Depth	120 mm
<b>Weights</b>	
Weight, approx.	470 g
<b>last modified:</b>	1/17/2021 