

### product type designation

product description

### PB M12 connector

M12 connector with pin insert, 5-pole, B-coded

M12 connection plug for ET 200 with axial cable outlet for assembly in the field, Male contact insert, 1 pack=5 units.



suitability for use

For connecting electrical PB bus cables to ET200

### transfer rate

transfer rate / with PROFIBUS

9.6 kbit/s ... 12 Mbit/s

### interfaces

number of electrical connections

- for PROFIBUS cables
- for network components or terminal equipment

1

1

type of electrical connection

- for PROFIBUS cables
- for network components or terminal equipment

Integrated screw-type contacts for 2-core PB installation cables  
M12 connector (male insert, 4-pin, B-coded)

type of electrical connection / FastConnect

No

### mechanical data

material / of the enclosure

metal

locking mechanism design

Screwed joint

tightening torque / for M12 round connector / maximum

0.6 N·m

connector coding / of the M12 circular connector

B

### design, dimensions and weights

type of cable outlet

180° cable outlet

width

19 mm

height

19 mm

depth

73 mm

net weight

40 g

connectable cable cross-section

6 ... 8 mm

connectable conductor cross-section

0.33 mm<sup>2</sup>

### ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-40 ... +70 °C

-40 ... +80 °C

-40 ... +80 °C

chemical resistance

- to water

resistant

protection class IP

IP65/67

### product features, product functions, product components / general

product feature

- silicon-free

Yes

product component

- strain relief

Yes

## standards, specifications, approvals

certificate of suitability

- RoHS conformity
- UL approval
- railway application in accordance with EN 50155

Yes  
No  
No

## further information / internet-Links

Internet-Link

- to web page: selection aid TIA Selection Tool
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Selection guide for cables and connectors
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>  
<http://www.siemens.com/simatic-net>  
<https://mall.industry.siemens.com>  
<http://www.siemens.com/industry/infocenter>  
<https://sie.ag/2QdlxcP>  
<http://automation.siemens.com/bilddb>  
<http://www.siemens.com/cax>  
<https://support.industry.siemens.com>

**last modified:**

6/30/2021 