SIEMENS

Data sheet

6ES7922-3BD00-0AU0

S7-300 FRONT CONNECTOR 20 TO DB	50F 3M

	cable with front connector for SIMATIC S7-300 20 pole (6ES7392-1AJ00- 0AA0) on 50-pole D-sub socket for ET200M; 0.50 mm2 length = 3 m	
target system	SIMATIC S7-300 PCS7 MTA	
product type designation	MTA	
product designation	Pre-assembled front connector MTA	
Product properties, functions, components / general / header		
wire length	3 m	
design of cable	Round cable	
material / of the connection cable sheath	PVC	
color / of cable sheath	Black	
outer diameter / of cable sheath	10.6 mm; bundled single cores	
conductor cross section / rated value	0.5 mm ²	
number of channels	20	
number of poles	20; of the front connector	
Operating data / header		
operating voltage / at DC		
 rated value 	24 V	
• maximum	30 V	
ambient temperature		
 during storage 	-30 +70 °C	
 during operation 	0 60 °C	
General data / header		
certificate of suitability / cULus approval	No	
suitability for interaction		
 input card PLC 	Yes	
 PLC output card 	No	
suitability for use		
 digital signal transmission 	No	
 analog signal transmission 	Yes	
type of electrical connection		
• in the field	Connector strip	
on enclosure	Screw-type terminal	
reference code / according to IEC 81346-2	W	
net weight	0.921 kg	

C