

product type designation

product description



KEY-PLUG SINEMA RC

Removable medium for activating SINEMA RC for SCALANCE M-800 / S615 and for simple device replacement in the event of a fault

KEY-PLUG SINEMA RC, Removable data storage medium for enabling of the connection to SINEMA Remote Connect for S615 and SCALANCE M for simple device replacement in event of fault and for Recording of configuration data.

suitability for use

Activation of SINEMA RC

ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-40 ... +75 °C
-40 ... +80 °C
-40 ... +80 °C

relative humidity

- at 25 °C / without condensation / during operation / maximum

95 %

protection class IP

IP20

design, dimensions and weights

width

24.3 mm

height

17 mm

depth

8.1 mm

net weight

5 g

design of the removable storage

- C-PLUG
- KEY-PLUG

No
Yes

product features, product functions, product components / general

storage capacity

256 Mibyte

standards, specifications, approvals

reference code

- according to IEC 81346-2:2019

CFA

further information / internet-Links

Internet-Link

- to website: TIA Selection Tool
- to web page: selection aid TIA Selection Tool
- to the website: IWLAN
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Selection guide for cables and connectors
- to website: Image database
- to website: CAX-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>
<http://www.siemens.com/snst>
<http://www.siemens.com/iwlan>
<http://www.siemens.com/simatic-net>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<https://sie.ag/2QdlxcP>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

5/20/2021

