

Article No. : 6SL3130-7TE25-5AA3



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data

Input

Number of phases	3 AC
Line voltage	342 ... 528 V
Line frequency	47 ... 63 Hz
Short-circuit strength ¹⁾	65 kA

Line power factor

in Active mode

Fundamental power factor cos phi _{1 2)}	1
Total	1

in Smart Mode

Fundamental power factor, minimal	.96
Total	0.65 ... 0.90

Overvoltage category Class III

DC link voltage³⁾

at 380 V ... 400 V AC, factory setting	600 V
at 400 V ... 415 V AC, factory setting	625 V
DC-link voltage	1.35 x line voltage (Smart Mode)
Electronics power supply with DC	24 V (-15 % / 20 %)

Connections

Line side

Design	M8 bolt (X1)
Conductor cross-section	2.50 ... 95.00 mm ² (AWG 14 ... AWG -2) (Alternatively 2 x 35 mm ²)
PE conductor	M6 screw

Line length, max.

Shielded	1,000 m (3,280.84 ft)
Unshielded	1,500 m (4,921.26 ft)

Mechanical data

Degree of protection	IP20 / UL open type
Type of construction	Booksize
Net weight	17.0 kg (37.48 lb)

Dimensions

Width	200 mm (7.87 in)
Height	380 mm (14.96 in)
Depth	270 mm (10.63 in)

Rated data

Infeed power

Rated value	55 kW (60 hp)
for S6 duty	71 kW
Maximum ⁶⁾	91 kW

Regenerative feedback power

Rated value	55 kW (60 hp)
for S6 duty	71 kW
Maximum ⁷⁾	91 kW

DC-link current

at 600 V DC	92 A
for S6 duty	121 A
Maximum ⁸⁾	152 A

Input current

at 380 V AC 3-phase	88 A
at 400 V AC 3-phase	84 A
at 480 V AC 3-phase	70 A
at 400 V S6 duty	108 A
at 400 V, maximum ⁹⁾	139 A

Current requirement at 24 V DC, maximum 1.9 A

Ampacity of the busbars

for electronics power supply at 24 V DC	20 A
for DC-link connection	200 A

DC link capacitance

of the Active Line Module	1,880 µF
of the drive system, maximum	20,000 µF

General technical specifications

Sound pressure level	60 dB
Losses ¹⁰⁾	0.95 kW

Ambient conditions

Ambient temperature in operation	0 ... 40 °C (32 ... 104 °F)
Cooling air throughput	0.044 m ³ /s (1.554 ft ³ /s)
Installation altitude	1,000 m (3,280.84 ft)
Type of cooling ¹¹⁾	Internal air cooling

RI suppression
Active Line Module + Active Interface Module: Category C3 according to EN 61800-3 up to 350 m (1148 ft) total cable length. With line filter: Category C2 according to EN 61800-3 up to 350 m (1148 ft) total cable length. Category C3 according to EN 61800-3 from 350 m to 1000 m (1148 ... 3281 ft) total cable length.

Standards

Compliance with standards	CE, cULus
---------------------------	-----------

Data sheet for Active Line Modules

Article No. : **6SL3130-7TE25-5AA3**

- ¹⁾ in conjunction with the recommended Class J fuse, or circuit breaker according to UL489 / CSA 22.2 No. 5-02
- ²⁾ Factory setting can be altered by inputting a reactive current setpoint (Active Mode)
- ³⁾ In Active Mode, the DC link voltage is regulated and can be adjusted as a voltage decoupled from the line voltage. In Smart Mode, the DC link voltage is kept in proportion to the line voltage at the mean rectified line voltage value. For line voltages of 416 ... 480 V AC, Active Mode can also be selected if the connected motors are suitable for > 650 V DC.
- ⁶⁾ Higher peak output is possible in combination with the Active Interface Module 6SL3100-0BE25-5AB0 (110 kW).
- ⁷⁾ Higher peak output is possible in combination with the Active Interface Module 6SL3100-0BE25-5AB0 (110 kW).
- ⁸⁾ Higher peak output is possible in combination with the Active Interface Module 6SL3100-0BE25-5AB0 (176 A).
- ⁹⁾ Higher peak output is possible in combination with the Active Interface Module 6SL3100-0BE25-5AB0 (168 A).
- ¹⁰⁾ Power loss of the Active Line Module with rated power including losses of the 24 V DC electronics power supply
- ¹¹⁾ Power units with intensified air cooling thanks to integrated fan