



Figure similar

### MLFB-Ordering data

6SL3210-5DE21-0UA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

### Rated data

#### Input

Number of phases	3 AC
Line voltage	380 ... 480 V -15 % +10 %
Line frequency	45 ... 66 Hz

#### Output

Rated power	2.50 kW
Rated current (IN)	7.80 A
Max. output current	23.40 A

#### Electronic power supply

Power supply	24 V ±10 %
--------------	------------

### General tech. specifications

Power loss	47.00 W
------------	---------

### Connections

#### Motor end

Conductor cross-section	2.5 mm <sup>2</sup>
-------------------------	---------------------

### Mechanical data

Degree of protection	IP20 / UL open type
Frame size	FSB
Net weight	2.45 kg ( 5.40 lb )
Width	100.0 mm ( 3.94 in )
Height	180.0 mm ( 7.09 in )
Depth	200.0 mm ( 7.87 in )

### Ambient conditions

Cooling	Forced-air cooling via fan
---------	----------------------------

Installation altitude	1000 m
-----------------------	--------

Cooling air requirement	0.005 m <sup>3</sup> /s ( 0.177 ft <sup>3</sup> /s )
-------------------------	--

#### Ambient temperature

Operation	0 ... 45 °C (32 ... 113 °F)
-----------	-----------------------------

Storage	-40 ... 70 °C (-40 ... 158 °F)
---------	--------------------------------

Transport	-40 ... 70 °C (-40 ... 158 °F)
-----------	--------------------------------

#### Relative humidity

Max. operation	90 %
----------------	------

### Standards

Compliance with standards	CE
---------------------------	----