



Figure similar

SIPLUS ET 200SP AI 4xRTD/TC high feature based on 6ES7134-6JD00-0CA1 with conformal coating, -40...+60 °C, analog input module, suitable for BU type A0, A1, color code CC00, channel diagnostics, 16-bit, +/-0.1%, 2/3/4-wire

General information	
Product type designation	AI 4xRTD/TC 2-/3-/4-wire HF
usable BaseUnits	BU type A0, A1
Color code for module-specific color identification plate	CC00
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	No
Operating mode	
<ul style="list-style-type: none"> <li>Oversampling</li> </ul>	No
<ul style="list-style-type: none"> <li>MSI</li> </ul>	No
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, max.	35 mA
Power loss	
Power loss, typ.	0.75 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>	8 byte; + 1 byte for QI information
Analog inputs	
Number of analog inputs	4
<ul style="list-style-type: none"> <li>For voltage measurement</li> </ul>	4
<ul style="list-style-type: none"> <li>For resistance/resistance thermometer measurement</li> </ul>	4
<ul style="list-style-type: none"> <li>For thermocouple measurement</li> </ul>	4
permissible input voltage for voltage input (destruction limit), max.	30 V
Constant measurement current for resistance-type transmitter, typ.	0.7 mA; 1.7 mA for Cu10 sensors
Cycle time (all channels), min.	Sum of the basic conversion times and additional processing times (depending on the parameterization of the active channels); for line compensation in case of a three-wire connection, an additional cycle is necessary
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
Input ranges (rated values), voltages	

<ul style="list-style-type: none"> <li>● -1 V to +1 V <ul style="list-style-type: none"> <li>— Input resistance (-1 V to +1 V)</li> </ul> </li> <li>● -250 mV to +250 mV <ul style="list-style-type: none"> <li>— Input resistance (-250 mV to +250 mV)</li> </ul> </li> <li>● -50 mV to +50 mV <ul style="list-style-type: none"> <li>— Input resistance (-50 mV to +50 mV)</li> </ul> </li> <li>● -80 mV to +80 mV <ul style="list-style-type: none"> <li>— Input resistance (-80 mV to +80 mV)</li> </ul> </li> </ul>	<p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p>
<b>Input ranges (rated values), thermocouples</b>	
<ul style="list-style-type: none"> <li>● Type B <ul style="list-style-type: none"> <li>— Input resistance (Type B)</li> </ul> </li> <li>● Type C <ul style="list-style-type: none"> <li>— Input resistance (Type C)</li> </ul> </li> <li>● Type E <ul style="list-style-type: none"> <li>— Input resistance (Type E)</li> </ul> </li> <li>● Type J <ul style="list-style-type: none"> <li>— Input resistance (type J)</li> </ul> </li> <li>● Type K <ul style="list-style-type: none"> <li>— Input resistance (Type K)</li> </ul> </li> <li>● Type L <ul style="list-style-type: none"> <li>— Input resistance (Type L)</li> </ul> </li> <li>● Type N <ul style="list-style-type: none"> <li>— Input resistance (Type N)</li> </ul> </li> <li>● Type R <ul style="list-style-type: none"> <li>— Input resistance (Type R)</li> </ul> </li> <li>● Type S <ul style="list-style-type: none"> <li>— Input resistance (Type S)</li> </ul> </li> <li>● Type T <ul style="list-style-type: none"> <li>— Input resistance (Type T)</li> </ul> </li> <li>● Type U <ul style="list-style-type: none"> <li>— Input resistance (Type U)</li> </ul> </li> <li>● Type TXK/TXK(L) to GOST <ul style="list-style-type: none"> <li>— Input resistance (Type TXK/TXK(L) to GOST)</li> </ul> </li> </ul>	<p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p>
<b>Input ranges (rated values), resistance thermometer</b>	
<ul style="list-style-type: none"> <li>● Cu 10</li> <li>● Ni 100 <ul style="list-style-type: none"> <li>— Input resistance (Ni 100)</li> </ul> </li> <li>● Ni 1000 <ul style="list-style-type: none"> <li>— Input resistance (Ni 1000)</li> </ul> </li> <li>● LG-Ni 1000 <ul style="list-style-type: none"> <li>— Input resistance (LG-Ni 1000)</li> </ul> </li> <li>● Ni 120 <ul style="list-style-type: none"> <li>— Input resistance (Ni 120)</li> </ul> </li> <li>● Ni 200 <ul style="list-style-type: none"> <li>— Input resistance (Ni 200)</li> </ul> </li> <li>● Ni 500 <ul style="list-style-type: none"> <li>— Input resistance (Ni 500)</li> </ul> </li> <li>● Pt 100 <ul style="list-style-type: none"> <li>— Input resistance (Pt 100)</li> </ul> </li> <li>● Pt 1000 <ul style="list-style-type: none"> <li>— Input resistance (Pt 1000)</li> </ul> </li> <li>● Pt 200 <ul style="list-style-type: none"> <li>— Input resistance (Pt 200)</li> </ul> </li> <li>● Pt 500 <ul style="list-style-type: none"> <li>— Input resistance (Pt 500)</li> </ul> </li> </ul>	<p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p> <p>Yes; 16 bit incl. sign 1 MΩ</p>
<b>Input ranges (rated values), resistors</b>	
<ul style="list-style-type: none"> <li>● 0 to 150 ohms <ul style="list-style-type: none"> <li>— Input resistance (0 to 150 ohms)</li> </ul> </li> <li>● 0 to 300 ohms <ul style="list-style-type: none"> <li>— Input resistance (0 to 300 ohms)</li> </ul> </li> <li>● 0 to 600 ohms <ul style="list-style-type: none"> <li>— Input resistance (0 to 600 ohms)</li> </ul> </li> <li>● 0 to 3000 ohms <ul style="list-style-type: none"> <li>— Input resistance (0 to 3000 ohms)</li> </ul> </li> </ul>	<p>Yes; 15 bit 1 MΩ</p> <p>Yes; 15 bit 1 MΩ</p> <p>Yes; 15 bit 1 MΩ</p> <p>Yes; 15 bit 1 MΩ</p>

<ul style="list-style-type: none"> <li>• 0 to 6000 ohms <ul style="list-style-type: none"> <li>— Input resistance (0 to 6000 ohms)</li> </ul> </li> <li>• PTC <ul style="list-style-type: none"> <li>— Input resistance (PTC)</li> </ul> </li> </ul>	Yes; 15 bit 1 MΩ Yes; 15 bit 1 MΩ
<b>Thermocouple (TC)</b>	
Temperature compensation	
<ul style="list-style-type: none"> <li>— parameterizable</li> <li>— Reference channel of the module</li> <li>— internal comparison point</li> <li>— Reference channel of the group</li> <li>— Number of reference channel groups</li> <li>— fixed reference temperature</li> </ul>	Yes Yes Yes; with BaseUnit type A1 Yes 4; Group 0 to 3 Yes
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	200 m; 50 m with thermocouples
<b>Analog value generation for the inputs</b>	
Measurement principle	integrating (Sigma-Delta)
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> <li>• Resolution with overrange (bit including sign), max.</li> <li>• Integration time, parameterizable</li> <li>• Basic conversion time, including integration time (ms) <ul style="list-style-type: none"> <li>— additional processing time for wire-break check</li> <li>— additional power line wire-break check</li> </ul> </li> <li>• Interference voltage suppression for interference frequency f1 in Hz</li> <li>• Conversion time (per channel)</li> </ul>	16 bit Yes 2 ms; In the ranges resistance thermometers, resistors and thermocouples 2 ms; for 3/4 wire transducer (resistance thermometer and resistor) 16.6 / 50 / 60 Hz 180 / 60 / 50 ms
Smoothing of measured values	
<ul style="list-style-type: none"> <li>• Number of smoothing levels</li> <li>• parameterizable</li> </ul>	4; None; 4/8/16 times Yes
<b>Encoder</b>	
Connection of signal encoders	
<ul style="list-style-type: none"> <li>• for voltage measurement</li> <li>• for resistance measurement with two-wire connection</li> <li>• for resistance measurement with three-wire connection</li> <li>• for resistance measurement with four-wire connection</li> </ul>	Yes Yes Yes Yes
<b>Errors/accuracies</b>	
Linearity error (relative to input range), (+/-)	0.01 %
Temperature error (relative to input range), (+/-)	0.005 %/K
Crosstalk between the inputs, min.	50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> <li>• Voltage, relative to input range, (+/-)</li> <li>• Resistance, relative to input range, (+/-)</li> </ul>	0.2 % 0.2 %
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> <li>• Voltage, relative to input range, (+/-)</li> <li>• Resistance, relative to input range, (+/-)</li> </ul>	0.05 % 0.05 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$ , $f_1 =$ interference frequency	
<ul style="list-style-type: none"> <li>• Series mode interference (peak value of interference &lt; rated value of input range), min.</li> <li>• Common mode voltage, max.</li> <li>• Common mode interference, min.</li> </ul>	70 dB 10 V 90 dB
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
Alarms	
<ul style="list-style-type: none"> <li>• Diagnostic alarm</li> <li>• Limit value alarm</li> </ul>	Yes Yes; two upper and two lower limit values in each case
Diagnoses	
<ul style="list-style-type: none"> <li>• Monitoring the supply voltage</li> <li>• Wire-break</li> </ul>	Yes Yes; channel by channel

<ul style="list-style-type: none"> <li>• Group error</li> <li>• Overflow/underflow</li> </ul>	<p>Yes</p> <p>Yes; channel by channel</p>
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>• Monitoring of the supply voltage (PWR-LED)</li> <li>• Channel status display</li> <li>• for channel diagnostics</li> <li>• for module diagnostics</li> </ul>	<p>Yes; green PWR LED</p> <p>Yes; green LED</p> <p>Yes; red LED</p> <p>Yes; green/red DIAG LED</p>
<b>Potential separation</b>	
<b>Potential separation channels</b>	
<ul style="list-style-type: none"> <li>• between the channels</li> <li>• between the channels and backplane bus</li> <li>• between the channels and the power supply of the electronics</li> </ul>	<p>No</p> <p>Yes</p> <p>Yes</p>
<b>Permissible potential difference</b>	
between the inputs (UCM)	10 V DC
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
<ul style="list-style-type: none"> <li>• horizontal installation, min.</li> <li>• horizontal installation, max.</li> <li>• vertical installation, min.</li> <li>• vertical installation, max.</li> </ul>	<p>-40 °C; = Tmin (incl. condensation/frost)</p> <p>60 °C; = Tmax; +70 °C with configured empty slots to the left and right of the module</p> <p>-40 °C; = Tmin (incl. condensation/frost)</p> <p>50 °C; = Tmax</p>
<b>Altitude during operation relating to sea level</b>	
<ul style="list-style-type: none"> <li>• Installation altitude above sea level, max.</li> <li>• Ambient air temperature-barometric pressure-altitude</li> </ul>	<p>5 000 m</p> <p>Tmin ... Tmax at 1 080 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)</p>
<b>Relative humidity</b>	
<ul style="list-style-type: none"> <li>• With condensation, tested in accordance with IEC 60068-2-38, max.</li> </ul>	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
<b>Resistance</b>	
<b>Coolants and lubricants</b>	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
<b>Use in stationary industrial systems</b>	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
— Against mechanical environmental conditions acc. to EN 60721-3-3	Yes; Class 3M8 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)
<b>Use on ships/at sea</b>	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
— Against mechanical environmental conditions acc. to EN 60721-3-6	Yes; Class 6M4 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)
<b>Usage in industrial process technology</b>	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
<b>Remark</b>	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
<b>Conformal coating</b>	
<ul style="list-style-type: none"> <li>• Coatings for printed circuit board assemblies acc. to EN 61086</li> </ul>	Yes; Class 2 for high reliability

- Protection against fouling acc. to EN 60664-3
- Military testing according to MIL-I-46058C, Amendment 7
- Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A

Yes; Type 1 protection  
 Yes; Discoloration of coating possible during service life  
 Yes; Conformal coating, Class A

#### Dimensions

Width	15 mm
Height	73 mm
Depth	58 mm

#### Weights

Weight, approx.	30 g
-----------------	------

**last modified:** 5/5/2021 