



SIPLUS ET 200SP AI Energy Meter 480VAC ST based on 6ES7134-6PA20-0BD0 with conformal coating, -40...+70 °C, analog input module, suitable for BU type D0, channel diagnostics

General information	
Product type designation	AI Energy Meter 480VAC ST
usable BaseUnits	BU type D0
Product function	
<ul style="list-style-type: none"> <li>• Voltage measurement                             <ul style="list-style-type: none"> <li>— with voltage transformer</li> </ul> </li> <li>• Current measurement                             <ul style="list-style-type: none"> <li>— without current transformer</li> <li>— with current transformer</li> </ul> </li> <li>• Energy measurement</li> <li>• Frequency measurement</li> <li>• Power measurement</li> <li>• Active power measurement</li> <li>• Reactive power measurement</li> <li>• I&amp;M data</li> <li>• Isochronous mode</li> </ul>	Yes Yes Yes No Yes Yes Yes Yes Yes Yes Yes; I&M0 to I&M3 No
Engineering with	
<ul style="list-style-type: none"> <li>• STEP 7 TIA Portal configurable/integrated from version</li> </ul>	see entry ID: 109746275
Operating mode	
<ul style="list-style-type: none"> <li>• cyclic measurement</li> <li>• acyclic measurement</li> <li>• Acyclic measured value access</li> <li>• Fixed measured value sets</li> <li>• Freely definable measured value sets</li> </ul>	Yes Yes Yes Yes Yes
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes
Installation type/mounting	
Mounting position	any
Supply voltage	
Design of the power supply	Supply via voltage measurement channel L1
Rated value (AC)	AC 100 - 277 V
permissible range, lower limit (AC)	90 V
permissible range, upper limit (AC)	293 V
Line frequency	
<ul style="list-style-type: none"> <li>• permissible range, lower limit</li> <li>• permissible range, upper limit</li> </ul>	47 Hz 63 Hz
Power loss	
Power loss, typ.	0.6 W
Address area	

Address space per module	
<ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>	268 byte; 256 byte input / 12 byte output
<b>Hardware configuration</b>	
Automatic encoding	
<ul style="list-style-type: none"> <li>Mechanical coding element</li> </ul>	Yes
<b>Time of day</b>	
Operating hours counter	
<ul style="list-style-type: none"> <li>present</li> </ul>	Yes
<b>Analog inputs</b>	
Cycle time (all channels), typ.	50 ms; Time for consistent update of all measured and calculated values (cyclic und acyclic data)
<b>Interrupts/diagnostics/status information</b>	
Alarms	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> <li>Limit value alarm</li> <li>Hardware interrupt</li> </ul>	<p>Yes</p> <p>Yes</p> <p>Yes; Monitoring of up to 16 freely selectable process values (exceeding or undershooting of value)</p>
Diagnostics indication LED	
<ul style="list-style-type: none"> <li>Monitoring of the supply voltage (PWR-LED)</li> <li>Channel status display</li> <li>for channel diagnostics</li> <li>for module diagnostics</li> </ul>	<p>Yes</p> <p>Yes; green LED</p> <p>Yes; red Fn LED</p> <p>Yes; green/red DIAG LED</p>
<b>Integrated Functions</b>	
Measuring functions	
<ul style="list-style-type: none"> <li>Measuring procedure for voltage measurement</li> <li>Measuring procedure for current measurement</li> <li>Type of measured value acquisition</li> <li>Curve shape of voltage</li> <li>Buffering of measured variables</li> <li>Parameter length</li> <li>Bandwidth of measured value acquisition</li> </ul>	<p>TRMS</p> <p>TRMS</p> <p>seamless</p> <p>Sinusoidal or distorted</p> <p>Yes</p> <p>74 byte</p> <p>2 kHz; Harmonics: 39 / 50 Hz, 32 / 60 Hz</p>
Measuring range	
— Frequency measurement, min.	45 Hz
— Frequency measurement, max.	65 Hz
Measuring inputs for voltage	
— Measurable line voltage between phase and neutral conductor	277 V
— Measurable line voltage between the line conductors	480 V
— Measurable line voltage between phase and neutral conductor, min.	90 V
— Measurable line voltage between phase and neutral conductor, max.	293 V
— Measurable line voltage between the line conductors, min.	155 V
— Measurable line voltage between the line conductors, max.	508 V
— Internal resistance line conductor and neutral conductor	3.4 MΩ
— Power consumption per phase	20 mW
— Impulse voltage resistance 1,2/50μs	1 kV
— Measurement category for voltage measurement in accordance with IEC 61010-2-030	CAT II; CAT III in case of guaranteed protection level of 1.5 kV
Measuring inputs for current	
— measurable relative current (AC), min.	1 %; Relative to the secondary rated current 5 A
— measurable relative current (AC), max.	100 %; Relative to the secondary rated current 5 A
— Continuous current with AC, maximum permissible	5 A; at > +60 °C max. permissible current 1 A per phase
— Apparent power consumption per phase for measuring range 5 A	0.6 VA
— Rated value short-time withstand current restricted to 1 s	100 A
— Input resistance measuring range 0 to 5 A	25 mΩ; At the terminal
— Surge strength	10 A; for 1 minute

— Zero point suppression	Parameterizable: 2 ... 250 mA, default 50 mA
<b>Accuracy class according to IEC 61557-12</b>	
— Measured variable voltage	0,2
— Measured variable current	0,2
— Measured variable apparent power	0.5
— Measured variable active power	0.5
— Measured variable reactive power	1
— Measured variable power factor	0.5
— Measured variable active energy	0.5
— Measured variable reactive energy	1
— Measured variable neutral current	0.5; calculated
— Measured variable phase angle	±1 °; not covered by IEC 61557-12
— Measured variable frequency	0.05
<b>Potential separation</b>	
Potential separation channels	
• between the channels and backplane bus	Yes; 3 700V AC (type test) CAT III
<b>Isolation</b>	
Isolation tested with	2 300V AC for 1 min. (type test)
<b>Ambient conditions</b>	
Ambient temperature during operation	
• horizontal installation, min.	-40 °C; = Tmin; < -25 °C min. permissible supply voltage 110 V AC
• horizontal installation, max.	70 °C; = Tmax; > +60 °C max. permissible current 1 A per phase
• vertical installation, min.	-40 °C; = Tmin
• vertical installation, max.	50 °C; = Tmax
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
<b>Resistance</b>	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
— Against mechanical environmental conditions acc. to EN 60721-3-3	Yes; Class 3M8 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
— Against mechanical environmental conditions acc. to EN 60721-3-6	Yes; Class 6M4 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Conformal coating	
• Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability

- Protection against fouling acc. to EN 60664-3
- Military testing according to MIL-I-46058C, Amendment 7
- Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A

Yes; Type 1 protection  
 Yes; Discoloration of coating possible during service life  
 Yes; Conformal coating, Class A

#### Dimensions

Width	20 mm
Height	73 mm
Depth	58 mm

#### Weights

Weight, approx.	45 g
-----------------	------

#### Other

##### Data for selecting a current transformer

- Burden power current transformer x/1A, min. As a function of cable length and cross section, see device manual
- Burden power current transformer x/5A, min. As a function of cable length and cross section, see device manual

**last modified:** 11/2/2021 