



Figure similar

SIPLUS S7-1200 SB 1221 4DI based on 6ES7221-3AD30-0XB0 with conformal coating, -40...+60 °C, start up -25 °C, digital inputs 4 DI 5 V DC 200 kHz

General information	
Product type designation	SB 1221, DI 4x5 V DC 200 kHz
Power loss	
Power loss, typ.	1 W
Digital inputs	
Number of digital inputs	4
Input voltage	
• Type of input voltage	DC
Input current	
• for signal "1", typ.	15 mA
Ambient conditions	
Ambient temperature during operation	
• min.	-40 °C; = Tmin (incl. condensation/frost); start-up @ -25 °C
• max.	60 °C; = Tmax
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to	Yes; Class 6S3 incl. sand, dust; *

EN 60721-3-6

Usage in industrial process technology

— Against chemically active substances acc. to EN 60654-4

Yes; Class 3 (excluding trichlorethylene)

— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04

Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)

Remark

— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04

\* The supplied plug covers must remain in place over the unused interfaces during operation!

Conformal coating

● Coatings for printed circuit board assemblies acc. to EN 61086

Yes; Class 2 for high reliability

● Protection against fouling acc. to EN 60664-3

Yes; Type 1 protection

● Military testing according to MIL-I-46058C, Amendment 7

Yes; Discoloration of coating possible during service life

● Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A

Yes; Conformal coating, Class A

Dimensions

Width

38 mm

Height

62 mm

Depth

21 mm

last modified:

9/16/2021 