



SIPLUS S7-1500 TM Posinput 2 based on 6ES7551-1AB00-0AB0 with conformal coating, -25...+70 °C, counting and position feedback module, 2 channels, for RS-422 incremental encoder or SSI absolute encoder, 2 DI, 2 DQ per channel

General information	
Product type designation	TM PosInput 2
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> <li>Isochronous mode</li> </ul>	Yes; I&M 0 Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V12 SP1 / V12 SP1
Installation type/mounting	
Rail mounting	Yes; S7-1500 mounting rail
Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> <li>permissible range, lower limit (DC)</li> <li>permissible range, upper limit (DC)</li> <li>Reverse polarity protection</li> </ul>	24 V 19.2 V 28.8 V Yes
Input current	
Current consumption, max.	75 mA; without load
Encoder supply	
Number of outputs	4; One 5V and 24V encoder supply per channel
5 V encoder supply	
<ul style="list-style-type: none"> <li>5 V</li> <li>Short-circuit protection</li> <li>Output current, max.</li> </ul>	Yes; 5.2 V ±2 % Yes 300 mA; Per channel
24 V encoder supply	
<ul style="list-style-type: none"> <li>24 V</li> <li>Short-circuit protection</li> <li>Output current, max.</li> </ul>	Yes; L+ (-0.8 V) Yes 300 mA; Per channel
Power	
Power available from the backplane bus	1.3 W
Power loss	
Power loss, typ.	5.5 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Inputs</li> <li>Outputs</li> </ul>	16 byte; Per channel 12 byte; per channel; 4 bytes for Motion Control
Digital inputs	
Number of digital inputs	4; 2 per channel
Digital inputs, parameterizable	Yes
Input characteristic curve in accordance with IEC 61131,	Yes

type 3

<b>Digital input functions, parameterizable</b>	
• Gate start/stop	Yes; only for pulse and incremental encoders
• Capture	Yes
• Synchronization	Yes; only for pulse and incremental encoders
• Freely usable digital input	Yes
<b>Input voltage</b>	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5 V
• for signal "1"	+11 to +30V
• permissible voltage at input, min.	-30 V
• permissible voltage at input, max.	30 V
<b>Input current</b>	
• for signal "1", typ.	2.5 mA
<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	
— parameterizable	Yes; none / 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms
— at "0" to "1", min.	6 µs; for parameterization "none"
— at "1" to "0", min.	6 µs; for parameterization "none"
for technological functions	
— parameterizable	Yes
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Digital outputs</b>	
Type of digital output	Transistor
Number of digital outputs	4; 2 per channel
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes; electronic/thermal
• Response threshold, typ.	1 A
Limitation of inductive shutdown voltage to	L+ (-33 V)
Controlling a digital input	Yes
<b>Digital output functions, parameterizable</b>	
• Switching tripped by comparison values	Yes
• Freely usable digital output	Yes
<b>Switching capacity of the outputs</b>	
• with resistive load, max.	0.5 A; Per digital output
• on lamp load, max.	5 W
<b>Load resistance range</b>	
• lower limit	48 Ω
• upper limit	12 kΩ
<b>Output voltage</b>	
• Type of output voltage	DC
• for signal "1", min.	23.2 V; L+ (-0.8 V)
<b>Output current</b>	
• for signal "1" rated value	0.5 A; Per digital output
• for signal "1" permissible range, max.	0.6 A; Per digital output
• for signal "1" minimum load current	2 mA
• for signal "0" residual current, max.	0.5 mA
<b>Output delay with resistive load</b>	
• "0" to "1", max.	50 µs
• "1" to "0", max.	50 µs
<b>Switching frequency</b>	
• with resistive load, max.	10 kHz
• with inductive load, max.	0.5 Hz; Acc. to IEC 60947-5-1, DC-13; observe derating curve
• on lamp load, max.	10 Hz
<b>Total current of the outputs</b>	
• Current per module, max.	2 A
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Encoder</b>	

<b>Encoder signals, incremental encoder (symmetrical)</b>	
<ul style="list-style-type: none"> <li>• Input voltage</li> <li>• Input frequency, max.</li> <li>• Counting frequency, max.</li> <li>• Cable length, shielded, max.</li> <li>• Signal filter, parameterizable</li> <li>• Incremental encoder with A/B tracks, 90° phase offset</li> <li>• Incremental encoder with A/B tracks, 90° phase offset and zero track</li> <li>• pulse encoder</li> <li>• Pulse encoder with direction</li> <li>• pulse encoder with one impulse signal per count direction</li> </ul>	RS 422 1 MHz 4 MHz; with quadruple evaluation 32 m; at 1 MHz Yes Yes Yes Yes Yes
<b>Encoder signals, incremental encoder (asymmetrical)</b>	
<ul style="list-style-type: none"> <li>• Input voltage</li> <li>• Input frequency, max.</li> <li>• Counting frequency, max.</li> <li>• Signal filter, parameterizable</li> <li>• Incremental encoder with A/B tracks, 90° phase offset</li> <li>• Incremental encoder with A/B tracks, 90° phase offset and zero track</li> <li>• pulse encoder</li> <li>• pulse encoder with direction</li> <li>• pulse encoder with one impulse signal per count direction</li> </ul>	5 V TTL 1 MHz 4 MHz; with quadruple evaluation Yes Yes Yes Yes Yes Yes
<b>Encoder signals, absolute encoder (SSI)</b>	
<ul style="list-style-type: none"> <li>• Input signal</li> <li>• Telegram length, parameterizable</li> <li>• Clock frequency, max.</li> <li>• Binary code</li> <li>• Gray code</li> <li>• Cable length, shielded, max.</li>   <li>• Parity bit, parameterizable</li> <li>• Monoflop time</li> <li>• Multiturn</li> <li>• Singleturn</li> </ul>	to RS-422 10 ... 40 bit 2 MHz; 125 kHz, 250 kHz, 500 kHz, 1 MHz, 1.5 MHz or 2 MHz Yes Yes 320 m; Cable length, RS-422 SSI absolute encoders, Siemens type 6FX2001-5, 24 V supply: 125 kHz, 320 meters shielded, max.; 250 kHz, 160 meters shielded, max.; 500 kHz, 60 meters shielded, max.; 1 MHz, 20 meters shielded, max. 1.5 MHz, 10 meters shielded, max.; 2 MHz, 8 meters shielded, max. Yes 16, 32, 48, 64 µs & automatic Yes Yes
<b>Interface types</b>	
<ul style="list-style-type: none"> <li>• TTL 5 V</li> <li>• RS 422</li> </ul>	Yes Yes
<b>Isochronous mode</b>	
Filtering and processing time (TCI), min.	130 µs; only for pulse and incremental encoders
Bus cycle time (TDP), min.	250 µs
<b>Interrupts/diagnostics/status information</b>	
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>• Diagnostic alarm</li> <li>• Hardware interrupt</li> </ul>	Yes Yes
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>• Monitoring the supply voltage</li> <li>• Wire-break</li> <li>• Short-circuit</li> <li>• A/B transition error at incremental encoder</li> <li>• Telegram error at SSI encoder</li> </ul>	Yes Yes Yes Yes Yes
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>• RUN LED</li> <li>• ERROR LED</li> <li>• MAINT LED</li> <li>• Monitoring of the supply voltage (PWR-LED)</li> <li>• Channel status display</li> <li>• for channel diagnostics</li> </ul>	Yes; green LED Yes; red LED Yes; Yellow LED Yes; green LED Yes; green LED Yes; red LED

## Integrated Functions

Counter	Yes
• Number of counters	2
• Counting frequency, max.	4 MHz; with quadruple evaluation
<b>Counting functions</b>	
• Can be used with TO High_Speed_Counter	Yes; only for pulse and incremental encoders
• Continuous counting	Yes
• Counter response parameterizable	Yes
• Hardware gate via digital input	Yes
• Software gate	Yes
• Event-controlled stop	Yes
• Synchronization via digital input	Yes
• Counting range, parameterizable	Yes
<b>Comparator</b>	
— Number of comparators	2; Per channel
— Direction dependency	Yes
— Can be changed from user program	Yes
<b>Position detection</b>	
• Incremental acquisition	Yes
• Absolute acquisition	Yes
• Suitable for S7-1500 Motion Control	Yes
<b>Measuring functions</b>	
• Measuring time, parameterizable	Yes
• Dynamic measurement period adjustment	Yes
• Number of thresholds, parameterizable	2
<b>Measuring range</b>	
— Frequency measurement, min.	0.04 Hz
— Frequency measurement, max.	4 MHz
— Cycle duration measurement, min.	0.25 µs
— Cycle duration measurement, max.	25 s
<b>Accuracy</b>	
— Frequency measurement	100 ppm; depending on measuring interval and signal evaluation
— Cycle duration measurement	100 ppm; depending on measuring interval and signal evaluation
— Velocity measurement	100 ppm; depending on measuring interval and signal evaluation
<b>Potential separation</b>	
<b>Potential separation channels</b>	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	No
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• horizontal installation, min.	-40 °C; = Tmin (incl. condensation/frost); start-up @ -25 °C
• horizontal installation, max.	70 °C; Please note derating for inductive loads
• vertical installation, min.	0 °C
• vertical installation, max.	40 °C; Please note derating for inductive loads
<b>Altitude during operation relating to sea level</b>	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
<b>Relative humidity</b>	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation
<b>Resistance</b>	
<b>Coolants and lubricants</b>	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
<b>Use in stationary industrial systems</b>	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *

— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
<b>Use on ships/at sea</b>	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
<b>Usage in industrial process technology</b>	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
<b>Remark</b>	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
<b>Conformal coating</b>	
<ul style="list-style-type: none"> <li>• Coatings for printed circuit board assemblies acc. to EN 61086</li> <li>• Protection against fouling acc. to EN 60664-3</li> <li>• Military testing according to MIL-I-46058C, Amendment 7</li> <li>• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A</li> </ul>	<p>Yes; Class 2 for high reliability</p> <p>Yes; Type 1 protection</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p>
<b>Decentralized operation</b>	
to SIMATIC S7-1500	Yes
to standard PROFINET controller	Yes
<b>Dimensions</b>	
Width	35 mm
Height	147 mm
Depth	129 mm
<b>Weights</b>	
Weight, approx.	325 g
<b>last modified:</b>	10/7/2021 