



SIMATIC ET 200SP, BusAdapter: BA SCRJ/FC, media converter FOC-CU
1x SCRJ FO connection and, 1x FastConnect (FC) connection

| General information | |
|--|--|
| Product type designation | BA SCRJ/FC |
| HW functional status | from FS04 |
| Interfaces | |
| Number of PROFINET interfaces | 1; 2 ports (SCRJ + FC) |
| Supports protocol for PROFINET IO | |
| <ul style="list-style-type: none"> Number of FC (FastConnect) connections Number of SCRJ ports | 1 |
| Cable length | |
| — PCF | 100 m |
| — Plastic FOC (POF) | 50 m |
| — PCF-GI | 250 m |
| — Cu conductors | 100 m |
| Ambient conditions | |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> horizontal installation, min. horizontal installation, max. vertical installation, min. vertical installation, max. | -25 °C 60 °C -25 °C 50 °C |
| Altitude during operation relating to sea level | |
| <ul style="list-style-type: none"> Installation altitude above sea level, max. | 5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual |
| Dimensions | |
| Width | 20 mm |
| Height | 69.5 mm |
| Depth | 59 mm |
| Weights | |
| Weight, approx. | 50 g |
| last modified: | 3/3/2023 |