



SIMATIC ET 200SP, BaseUnit BU15-P16+A0+2D, BU type A0, Pack quantity: 10 units, Push-in terminals, without AUX terminals, New load group, WxH: 15x 117 mm

General information	
Product type designation	BU type A0
HW functional status	From FS06
Supply voltage	
Rated value (DC)	24 V
external protection for power supply lines	Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic
Mains filter	
<ul style="list-style-type: none"> integrated 	Yes
Current carrying capacity	
For P1 and P2 bus, max.	10 A
For process terminals, max.	2 A
Hardware configuration	
Formation of potential groups	
<ul style="list-style-type: none"> New potential group 	Yes
<ul style="list-style-type: none"> Potential group continued from the left 	No
Slots	
<ul style="list-style-type: none"> Number of slots 	1; Type A0
Potential separation	
between the potential groups	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> horizontal installation, min. 	-30 °C
<ul style="list-style-type: none"> horizontal installation, max. 	60 °C
<ul style="list-style-type: none"> vertical installation, min. 	-30 °C
<ul style="list-style-type: none"> vertical installation, max. 	50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> Installation altitude above sea level, max. 	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Accessories	
Color coding labels	
<ul style="list-style-type: none"> for process terminals 	CC00 to CC09
<ul style="list-style-type: none"> for AUX terminals 	does not exist
<ul style="list-style-type: none"> for add-on terminals 	does not exist
connection method / header	
Terminals	
<ul style="list-style-type: none"> Terminal type 	Push-in terminal
<ul style="list-style-type: none"> system-integrated shield connection 	Yes; Optional
<ul style="list-style-type: none"> Conductor cross-section, min. 	0.14 mm ² ; AWG 26

- Conductor cross-section, max. 2.5 mm²; AWG 14
- Number of process terminals to I/O module 16
- Number of terminals to AUX bus 0
- Number of add-on terminals 0
- Number of terminals with connection to P1 and P2 bus 2

Dimensions

Width	15 mm
Height	117 mm
Depth	35 mm

Weights

Weight, approx.	40 g
-----------------	------

last modified: 1/20/2023 