



SIMATIC S7-1500R, CPU 1515R-2 PN central processing unit with work memory 500 KB for program and 3 MB for data, 1st interface: PROFINET RT with 2-port switch, 2nd interface: PROFINET, SIMATIC Memory Card required

| General information  |   |
|--|---|
| Product type designation   | CPU 1515R-2 PN                                  |
| HW functional status   | FS01  |
| Firmware version   | V2.9  |
| Product function   |   |
| <ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>   | Yes; I&M0 to I&M3                               |
| <ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>                                       | No  |
| Engineering with   |   |
| <ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul> | V17 (FW V2.9) / V16 (FW V2.8) / V15.1 (FW V2.6) |
| Display  |   |
| Screen diagonal [cm]   | 6.1 cm  |
| Control elements   |   |
| Number of keys   | 6   |
| Mode selector switch   | 1   |
| Supply voltage   |   |
| Rated value (DC)   | 24 V  |
| permissible range, lower limit (DC)  | 19.2 V  |
| permissible range, upper limit (DC)  | 28.8 V  |
| Reverse polarity protection  | Yes   |
| Mains buffering  |   |
| <ul style="list-style-type: none"> <li>Mains/voltage failure stored energy time</li> </ul>               | 5 ms  |
| Input current  |   |
| Current consumption (rated value)  | 0.8 A   |
| Inrush current, max.   | 2.4 A   |
| $I^2t$   | 0.02 A <sup>2</sup> ·s                          |
| Power loss   |   |
| Power loss, typ.   | 6.3 W   |
| Memory   |   |
| Number of slots for SIMATIC memory card  | 1   |
| SIMATIC memory card required   | Yes   |
| Work memory  |   |
| <ul style="list-style-type: none"> <li>integrated (for program)</li> </ul>                               | 500 kbyte                                       |
| <ul style="list-style-type: none"> <li>integrated (for data)</li> </ul>                                  | 3 Mbyte   |
| Load memory  |   |
| <ul style="list-style-type: none"> <li>Plug-in (SIMATIC Memory Card), max.</li> </ul>                    | 32 Gbyte  |
| Backup   |   |
| <ul style="list-style-type: none"> <li>maintenance-free</li> </ul>                                       | Yes   |
| CPU processing times   |   |
| for bit operations, typ.   | 60 ns   |

|                                     |        |
|-------------------------------------|--------|
| for word operations, typ.           | 72 ns  |
| for fixed point arithmetic, typ.    | 96 ns  |
| for floating point arithmetic, typ. | 384 ns |

#### CPU-blocks

|                                    |   |
|------------------------------------|---|
| Number of elements (total)         | 8 000; Blocks (OB, FB, FC, DB) and UDTs                                     |
| <b>DB</b>                          |   |
| • Number range                     | Number range: 1 to 59 999   |
| • Size, max.                       | 3 Mbyte; For non-optimized block accesses, the max. size of the DB is 64 KB |
| <b>FB</b>                          |   |
| • Number range                     | 0 ... 65 535  |
| • Size, max.                       | 500 kbyte   |
| <b>FC</b>                          |   |
| • Number range                     | 0 ... 65 535  |
| • Size, max.                       | 500 kbyte   |
| <b>OB</b>                          |   |
| • Size, max.                       | 500 kbyte   |
| • Number of free cycle OBs         | 100   |
| • Number of time alarm OBs         | 20  |
| • Number of delay alarm OBs        | 20  |
| • Number of cyclic interrupt OBs   | 20  |
| • Number of process alarm OBs      | 50  |
| • Number of startup OBs            | 100   |
| • Number of asynchronous error OBs | 4   |
| • Number of synchronous error OBs  | 2   |
| • Number of diagnostic alarm OBs   | 1   |
| <b>Nesting depth</b>               |   |
| • per priority class               | 24  |

#### Counters, timers and their retentivity

|                    |                                       |
|--------------------|---------------------------------------|
| <b>S7 counter</b>  |                                       |
| • Number           | 2 048                                 |
| <b>Retentivity</b> |                                       |
| — adjustable       | Yes                                   |
| <b>IEC counter</b> |                                       |
| • Number           | Any (only limited by the main memory) |
| <b>Retentivity</b> |                                       |
| — adjustable       | Yes                                   |
| <b>S7 times</b>    |                                       |
| • Number           | 2 048                                 |
| <b>Retentivity</b> |                                       |
| — adjustable       | Yes                                   |
| <b>IEC timer</b>   |                                       |
| • Number           | Any (only limited by the main memory) |
| <b>Retentivity</b> |                                       |
| — adjustable       | Yes                                   |

#### Data areas and their retentivity

|   |   |
|---|---|
| Retentive data area (incl. timers, counters, flags), max. | 512 kbyte   |
| <b>Flag</b>   |   |
| • Size, max.  | 16 kbyte  |
| • Number of clock memories                                | 8; 8 clock memory bit, grouped into one clock memory byte |
| <b>Data blocks</b>  |   |
| • Retentivity adjustable                                  | Yes   |
| • Retentivity preset                                      | No  |
| <b>Local data</b>   |   |
| • per priority class, max.                                | 64 kbyte; max. 16 KB per block                            |


#### Address area

|                             |  |
|-----------------------------|--|
| Number of IO modules        | 4 096; max. number of modules / submodules     |
| <b>I/O address area</b>     |  |
| • Inputs                    | 32 kbyte; All inputs are in the process image  |
| • Outputs                   | 32 kbyte; All outputs are in the process image |
| per integrated IO subsystem |  |
| — Inputs (volume)           | 8 kbyte  |
| — Outputs (volume)          | 8 kbyte  |

|  |  |
|--|--|
| <b>Subprocess images</b>                 |  |
| • Number of subprocess images, max.      | 32   |
| <b>Hardware configuration</b>            |  |
| Number of distributed IO systems         | 1  |
| <b>Number of IO Controllers</b>          |  |
| • integrated                             | 1  |
| <b>Time of day</b>                       |  |
| <b>Clock</b>                             |  |
| • Type                                   | Hardware clock   |
| • Backup time                            | 6 wk; At 40 °C ambient temperature, typically  |
| • Deviation per day, max.                | 10 s; Typ.: 2 s  |
| <b>Operating hours counter</b>           |  |
| • Number                                 | 16   |
| <b>Clock synchronization</b>             |  |
| • supported                              | Yes  |
| • on Ethernet via NTP                    | Yes  |
| <b>Interfaces</b>                        |  |
| Number of PROFINET interfaces            | 2  |
| <b>1. Interface</b>                      |  |
| <b>Interface types</b>                   |  |
| • RJ 45 (Ethernet)                       | Yes; X1  |
| • Number of ports                        | 2  |
| • integrated switch                      | Yes  |
| <b>Protocols</b>                         |  |
| • IP protocol                            | Yes; IPv4  |
| • PROFINET IO Controller                 | Yes  |
| • PROFINET IO Device                     | No   |
| • SIMATIC communication                  | Yes; Only Server   |
| • Open IE communication                  | Yes  |
| • Web server                             | No   |
| • Media redundancy                       | Yes  |
| <b>PROFINET IO Controller</b>            |  |
| <b>Services</b>                          |  |
| — PG/OP communication                    | Yes  |
| — Isochronous mode                       | No   |
| — IRT                                    | No   |
| — PROFIenergy                            | Yes  |
| — Number of connectable IO Devices, max. | 64   |
| — Updating times                         | The minimum value of the update time also depends on communication share set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data |
| <b>Update time for RT</b>                |  |
| — for send cycle of 1 ms                 | 1 ms to 512 ms   |
| <b>2. Interface</b>                      |  |
| <b>Interface types</b>                   |  |
| • RJ 45 (Ethernet)                       | Yes; X2  |
| • Number of ports                        | 1  |
| • integrated switch                      | No   |
| <b>Protocols</b>                         |  |
| • IP protocol                            | Yes; IPv4  |
| • PROFINET IO Controller                 | No   |
| • PROFINET IO Device                     | No   |
| • SIMATIC communication                  | Yes; Only Server   |
| • Open IE communication                  | Yes  |
| • Web server                             | No   |
| • Media redundancy                       | No   |
| <b>Interface types</b>                   |  |
| <b>RJ 45 (Ethernet)</b>                  |  |
| • 100 Mbps                               | Yes  |
| • Autonegotiation                        | Yes  |
| • Autocrossing                           | Yes  |
| • Industrial Ethernet status LED         | Yes  |

| Protocols  |   |
|--|---|
| PROFIsafe  | No  |
| Number of connections                                |   |
| • Number of connections, max.                        | 108   |
| • Number of connections reserved for ES/HMI/web      | 10  |
| • Number of S7 routing paths                         | 16  |
| Redundancy mode                                      |   |
| Media redundancy                                     |   |
| — MRP  | Yes; MRP Automanager according to IEC 62439-2 Edition 2.0                             |
| — MRP interconnection, supported                     | Yes; as MRP ring node according to IEC 62439-2 Edition 3.0                            |
| — MRPD   | No  |
| — Switchover time on line break, typ.                | 200 ms; PROFINET MRP  |
| — Number of stations in the ring, max.               | 50; Only 16 are recommended, however  |
| SIMATIC communication                                |   |
| • PG/OP communication                                | Yes; encryption with TLS V1.3 pre-selected  |
| • S7 routing   | Yes   |
| • S7 communication, as server                        | Yes   |
| • S7 communication, as client                        | No  |
| Open IE communication                                |   |
| • TCP/IP   | Yes   |
| — Data length, max.                                  | 64 kbyte  |
| — several passive connections per port, supported    | Yes   |
| • ISO-on-TCP (RFC1006)                               | Yes   |
| — Data length, max.                                  | 64 kbyte  |
| • UDP  | Yes   |
| — Data length, max.                                  | 2 kbyte; 1 472 bytes for UDP broadcast  |
| — UDP multicast                                      | Yes; Max. 5 multicast circuits  |
| • DHCP   | No  |
| • DNS  | Yes   |
| • SNMP   | Yes   |
| • DCP  | Yes   |
| • LLDP   | Yes   |
| Web server   |   |
| • HTTP   | No  |
| • HTTPS  | No  |
| OPC UA   |   |
| • OPC UA Client                                      | No  |
| • OPC UA Server                                      | No  |
| Further protocols                                    |   |
| • MODBUS   | Yes; MODBUS TCP   |
| Isochronous mode                                     |   |
| Equidistance   | No  |
| S7 message functions                                 |   |
| Number of login stations for message functions, max. | 64  |
| Program alarms                                       | Yes   |
| Number of configurable program messages, max.        | 10 000; Program messages are generated by the "Program_Alarm" block, ProDiag or GRAPH |
| Number of loadable program messages in RUN, max.     | 5 000   |
| Number of simultaneously active program alarms       |   |
| • Number of program alarms                           | 800   |
| • Number of alarms for system diagnostics            | 200   |
| Test commissioning functions                         |   |
| Joint commission (Team Engineering)                  | No  |
| Status block   | Yes; up to 8 simultaneously   |
| Single step  | No  |
| Number of breakpoints                                | 8; Breakpoints are only supported in RUN-Solo status                                  |
| Status/control                                       |   |
| • Status/control variable                            | Yes   |
| • Variables  | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters                  |
| • Number of variables, max.                          |   |
| — of which status variables, max.                    | 200; per job  |
| — of which control variables, max.                   | 200; per job  |

|   |  |
|---|--|
| <b>Forcing</b>  |  |
| <ul style="list-style-type: none"> <li>• Forcing</li> <li>• Forcing, variables</li> <li>• Number of variables, max.</li> </ul>  | Yes<br>Peripheral inputs/outputs<br>200  |
| <b>Diagnostic buffer</b>  |  |
| <ul style="list-style-type: none"> <li>• present</li> <li>• Number of entries, max.<br/>— of which powerfail-proof</li> </ul>   | Yes<br>3 200<br>500  |
| <b>Traces</b>   |  |
| <ul style="list-style-type: none"> <li>• Number of configurable Traces</li> <li>• Memory size per trace, max.</li> </ul>  | 4<br>512 kbyte   |
| <b>Interrupts/diagnostics/status information</b>  |  |
| <b>Diagnostics indication LED</b>   |  |
| <ul style="list-style-type: none"> <li>• RUN/STOP LED</li> <li>• ERROR LED</li> <li>• MAINT LED</li> <li>• Connection display LINK TX/RX</li> </ul>   | Yes<br>Yes<br>Yes<br>Yes   |
| <b>Supported technology objects</b>   |  |
| Motion Control  | No   |
| Controller  |  |
| <ul style="list-style-type: none"> <li>• PID_Compact</li> <li>• PID_3Step</li> <li>• PID-Temp</li> </ul>  | Yes; Universal PID controller with integrated optimization<br>Yes; PID controller with integrated optimization for valves<br>Yes; PID controller with integrated optimization for temperature                            |
| Counting and measuring  | Yes  |
| <ul style="list-style-type: none"> <li>• High-speed counter</li> </ul>  | No   |
| <b>Ambient conditions</b>   |  |
| <b>Ambient temperature during operation</b>   |  |
| <ul style="list-style-type: none"> <li>• horizontal installation, min.</li> <li>• horizontal installation, max.</li> <li>• vertical installation, min.</li> <li>• vertical installation, max.</li> </ul>  | 0 °C<br>60 °C; Display: 50 °C, at an operating temperature of typically 50 °C, the display is switched off<br>0 °C<br>40 °C; Display: 40 °C, at an operating temperature of typically 40 °C, the display is switched off |
| <b>Ambient temperature during storage/transportation</b>  |  |
| <ul style="list-style-type: none"> <li>• min.</li> <li>• max.</li> </ul>  | -40 °C<br>70 °C  |
| <b>Altitude during operation relating to sea level</b>  |  |
| <ul style="list-style-type: none"> <li>• Installation altitude above sea level, max.</li> </ul>   | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual   |
| <b>configuration / header</b>   |  |
| <b>configuration / programming / header</b>   |  |
| <b>Programming language</b>   |  |
| <ul style="list-style-type: none"> <li>— LAD</li> <li>— FBD</li> <li>— STL</li> <li>— SCL</li> <li>— CFC</li> <li>— GRAPH</li> </ul>  | Yes<br>Yes<br>Yes<br>Yes<br>No<br>Yes  |
| <b>Know-how protection</b>  |  |
| <ul style="list-style-type: none"> <li>• User program protection/password protection</li> <li>• Copy protection</li> <li>• Block protection</li> </ul>  | Yes<br>No<br>Yes   |
| <b>Access protection</b>  |  |
| <ul style="list-style-type: none"> <li>• protection of confidential configuration data</li> <li>• Password for display</li> <li>• Protection level: Write protection</li> <li>• Protection level: Read/write protection</li> <li>• Protection level: Complete protection</li> </ul> | Yes<br>Yes<br>Yes<br>Yes<br>Yes  |
| <b>programming / cycle time monitoring / header</b>   |  |
| <ul style="list-style-type: none"> <li>• lower limit</li> <li>• upper limit</li> </ul>  | adjustable minimum cycle time<br>adjustable maximum cycle time   |
| <b>Dimensions</b>   |  |
| Width   | 70 mm  |
| Height  | 147 mm   |

|                       |  |
|-----------------------|--|
| Depth                 | 129 mm   |
| <b>Weights</b>        |  |
| Weight, approx.       | 830 g  |
| <b>last modified:</b> | 4/1/2022  |