



FRONT CONN. MOD.(2A DIGITAL 1X8) S7-1500

Front connector module with 1x16 pole IDC connector for digital 2 A output modules of the S7-1500 Potential supply over Push-in terminal

target system
suitability for use
product type designation
product designation

SIMATIC S7-1500
2A Output module
Fully modular connection
Front connector module

Operating data / header

operating voltage	24 V
• at DC / rated value	24 V
• rated value	60 V
• at DC / maximum	1 A
current / rated value	1 A
continuous current / at DC / per plug-in contact / maximum	3 A; for mounting position horizontal
total current / maximum	0 ... 60 °C
operating temperature	0 ... 60 °C
ambient temperature	-40 ... +70 °C
• during operation	40; of the front connector
• during storage	replacement for S7-1500 40 pole
number of poles	1
manufacturer's article number / of device connector / usable	Plug-in connection
number of the plug contacts / of the electrical connection	16; the IDC connector for the connection cable
type of electrical connection / for connecting cable	at the top
number of poles / at the 1st interface	Push-In terminal
position / of the terminal	4; 2 x 1 x L+, 2 x 1 x M
type of electrical connection / for power supply	3.5 mm
number of terminals	No
width of screwdriver blade	No
product component / required / end cover plate	2; Connection for internal system: Combination of 1 or 2 Wires until the sum total of cross sections be achieved in a ferrule.
number of cables / per connection	8 mm
stripped length	No
type of connectable conductor cross-sections / solid	0.25 ... 1.5 mm ² ; End sleeve according to DIN 46228/1 or DIN 46228/4 with plastic collar max. 0.75 mm ²
connectable conductor cross-section	0.5 ... 1.5 mm ²
• for flexible conductor / with core end processing	0.5 ... 1.5 mm ²
• stranded	0.25 ... 1.5 mm ²
• finely stranded / without core end processing	
• finely stranded / with core end processing	
type of wire end sleeve	Length 8mm to 9mm
• without plastic sleeve / according to DIN 46228-1	Length 8mm to 9mm
• with plastic sleeve / according to DIN 46228-4	
outer diameter / of the wire insulation	3.1 mm; to the connection of the supply terminal
wire length / maximum	30 m; between front connector module and terminal module

General data / header

mounting type	direct mounting
degree of pollution	2
overvoltage category	2
design tested acc. to type of protection / EEx e	No
certificate of suitability / cULus approval	Yes
reference code / according to IEC 81346-2	XG
material / of the insulating body	other
color / of the enclosure	black
product feature / transparent	No
net weight	0.099 kg

last modified:

7/12/2022 