SIEMENS

Data sheet

6ES7922-5BD20-0HC0



S7-1500 FRONTCON. 40CORES HALOG.-FR 3.2M

Front connector for SIMATIC S7-1500 40 pole (6ES7592-1AM00-0XB0) with 40 single cores 0.5 mm2 Core type H05Z-K (halogen-free) Screw version L = 3.2 m

target system suitability for use product type designation product designation

SIMATIC S7-1500 Digital I/O modules Flexible connection

Front connector with single cores

Product properties, functions, components / general / header

connector type wire length design of cable

material / of the connection cable sheath

color / of cable sheath RAL color number

outer diameter / of cable sheath conductor cross section / rated value

marking / of cores

type of connecting terminal number of channels number of poles

6ES7592-1AM00-0XB0

3.2 m H05Z-K

Polyolefin basis halogen-free

blue **RAL 5010**

2.2 mm; bundled single cores

0.5 mm²

Number consecutively from 1 to 40 in white adapter contact = core

number

Screw-type terminal

40; of the front connector

Operating data / header

operating voltage / at DC

24 V rated value 30 V continuous current / with simultaneous load on all cores / 1.5 A at DC / maximum permissible

ambient temperature

• during storage during operation 0 ... 60 °C

-15 ... +60 °C

General data / header

certificate of suitability / cULus approval

suitability for interaction

- input card PLC
- PLC output card

suitability for use

- digital signal transmission
- analog signal transmission

type of electrical connection

- in the field
- on enclosure

reference code / according to IEC 81346-2

net weight

No

Yes

Yes

Yes No

other

Screw-type terminal

WG 1.54 kg