# **SIEMENS**

#### **Data sheet**

## 6ES7922-5BG50-0HB0



#### S7-1500 FRONTCONN. 20 CORES HALOFR 6.5M

Front connector for SIMATIC S7-1500 40 pole (6ES7592-1AM00-0XB0) with 20 single cores 0.5 mm2 (1-20) Core type H05Z-K (halogen-free) Screw version L = 6.5 m

target system suitability for use product type designation product designation

**SIMATIC S7-1500** Digital I/O modules Flexible connection

Front connector with single cores

Product pro	perties.	functions.	component	ts / o	ieneral /	header

connector type wire length design of cable

material / of the connection cable sheath

color / of cable sheath RAL color number

outer diameter / of cable sheath conductor cross section / rated value

marking / of cores

type of connecting terminal number of channels number of poles

6ES7592-1AM00-0XB0

6.5 m H05Z-K

Polyolefin basis halogen-free

blue **RAL 5010** 

2.2 mm; bundled single cores

0.5 mm<sup>2</sup>

Number consecutively from 1 to 20 in white adapter contact = core

number

Screw-type terminal

20

40; of the front connector

## Operating data / header

operating voltage / at DC

24 V rated value 30 V continuous current / with simultaneous load on all cores / 1.5 A at DC / maximum permissible

ambient temperature

-15 ... +60 °C • during storage during operation 0 ... 60 °C

General data / header

certificate of suitability / cULus approval

suitability for interaction

• input card PLC

 PLC output card suitability for use

• digital signal transmission

• analog signal transmission

type of electrical connection

• in the field

• on enclosure reference code / according to IEC 81346-2

net weight

No

Yes

Yes

Yes No

other

Screw-type terminal

WG 1.55 kg

7