

CONNECT. CABLE 40P TO 50P 1.0M UNSHIELD

Connecting cable unshielded for SIMATIC S7-1500 64 I/O between I/O modul X10 or X11 and connection module 32 I/O 0.14 mm<sup>2</sup>, L = 1.0m, 1 pcs. 40 of 50 pole IDC connector



Figure similar

target system	SIMATIC S7-1500
suitability for use	Digital I/O modules
product type designation	Fully modular connection
product designation	Pre-assembled round cable

### Operating data / header

operating voltage / at DC	
<ul style="list-style-type: none"> <li>• rated value</li> <li>• maximum</li> </ul>	24 V 60 V
ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> <li>• during storage</li> </ul>	-30 ... +60 °C -30 ... +70 °C

### General data / header

suitability for interaction	
<ul style="list-style-type: none"> <li>• input card PLC</li> <li>• PLC output card</li> </ul>	Yes Yes
suitability for use	
<ul style="list-style-type: none"> <li>• digital signal transmission</li> <li>• analog signal transmission</li> </ul>	Yes No

### Product properties, functions, components / general / header

number of channels	32
design of cable	Round cable
wire length	1 m
number of poles	40
number of conductors / of connection cable	40
conductor cross section / rated value	0.14 mm <sup>2</sup>
color / of cable sheath	Black
outer diameter / of cable sheath	10.3 mm
material / of the connection cable sheath	PVC
connector type	IDC connector
type of electrical connection / on enclosure	Connector strip
number of poles / at the 1st interface	40; control page
type of electrical connection / in the field	Connector strip
number of poles / at the 2nd interface	50; on the connection module
certificate of suitability / cULus approval	No
reference code / according to IEC 81346-2	WG
net weight	0.2 kg

last modified: 7/13/2022 