



Figure similar

TERM. BLOCK TPOO W. LED PUSH-IN TERM.

Connection module TPOO with optocoupler 24 VDC, Output 8 NO contacts 24V DC/4 A Overload and short circuit-proof, with LED Push-in terminal VPE = 1 unit 16 pole IDC connector f. cable

target system	SIMATIC S7-300 / 1500
suitability for use	Digital output module
product type designation	Fully modular connection
product designation	Connection module

Operating data / header

operating voltage	24 V; for coil
<ul style="list-style-type: none"> at DC / rated value rated value at DC / maximum at AC / rated value 	50 V
current / rated value	28.8 V
continuous current / at DC / per signal cable / maximum	for coil
total current / maximum	1 A
switching capacity current / of the contacts / with resistive load / maximum	4 A
operating temperature	32 A; any, except overhead; voltage feed each group of four max. 16A
ambient temperature	4 A; for 24V DC
<ul style="list-style-type: none"> during operation during storage 	0 ... 60 °C
number of terminal levels	0 ... 60 °C
number of terminal points / per terminal level	-40 ... +70 °C
number of terminals	1
type of connecting terminal	1
type of electrical connection / for actuators and sensors	22; 8 x O; 2 x L+, 2 x M; 10 x special terminals
position / of the terminal	Push-In
design of LED initiator/actuator terminal	Push-In
width of screwdriver blade	Top
design of terminal / terminal levels internally linked	Push-In
product component	3.5 mm
<ul style="list-style-type: none"> PE connection shield connection disconnecter required / end cover plate 	No
product function / infeed function	No
product feature / cross-connectable	No
type of switching contact	No
operating frequency / maximum	No
number of cables / per connection	Yes
type of connectable conductor cross-sections / solid	No
connectable conductor cross-section	Optocoupler
	500 1/s
	2; Connection for internal system: Combination of 1 or 2 Wires until the sum total of cross sections be achieved in a ferrule.
	No

<ul style="list-style-type: none"> • for flexible conductor / with core end processing 	0.2 ... 2.5 mm ² ; End sleeve according to DIN 46228/1 or DIN 46228/4 with plastic collar
<ul style="list-style-type: none"> • stranded 	0.2 ... 2.5 mm ²
<ul style="list-style-type: none"> • finely stranded / without core end processing 	0.2 ... 2.5 mm ²
<ul style="list-style-type: none"> • finely stranded / with core end processing 	0.2 ... 2.5 mm ²
number of poles / at the 1st interface	16; the IDC connector for the connection cable
type of electrical connection / for connecting cable	Plug-in connection
number of the plug contacts / of the electrical connection	1
wire length / maximum	30 m; between front connector module and Connection module

General data / header

mounting type	DIN rail 35 mm, DIN rail 15 mm
installation or assembly note	any, head excepted
mounting position	any
degree of pollution	2
overvoltage category	2
combustibility class according to UL 94	V1
insulation material	other
design tested acc. to type of protection / EEx e	No
certificate of suitability / cULus approval	Yes
reference code / according to IEC 81346-2	XG
color	
<ul style="list-style-type: none"> • of the enclosure 	grey
<ul style="list-style-type: none"> • of the light source 	other
length	76 mm
height / of the enclosure	76 mm
width / of the enclosure	130 mm
depth / of the enclosure	60 mm
height / with lowest-profile installation	60 mm
net weight	0.25 kg

