

## Data sheet for SIMOTICS S-1FL6



Figure similar

MLFB-Ordering data

1FL6066-1AC61-2AA1

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Engineering data		Mechanical data			
Rated speed	2000 rpm	Motor type	High Inertia		
Rated torque (100 K)	8.36 Nm	Motor type	Permanent-magnet synchronous motor		
Rated current	5.3 A	Shaft height	65		
Rated power	1.75 kW / 2.38 hp	Encoder system	Incremental encoder TTL, 2500 S/R (13 bit)		
Max. speed	3000 rpm	Cooling	Natural cooling		
Maximum torque	25.10 Nm	Shaft end	Feather key		
Max. current	15.9 A	Radial runout tolerance	Class N		
Static torque	11.00 Nm	Vibration severity grade	Grade A		
Moment of inertia	22.600 kgcm <sup>2</sup>	Degree of protection	IP65		
<b>Physical constants</b>		Design acc. to Code I	IM B5 (IM V1, IM V3)		
		Torque constant	1.70 Nm/A	Connection type	Angular connector (rotatable)
		Thermal class	B (130 °C)		
Net weight	11.10 kg	<b>Ambient conditions</b>			
<b>Ambient conditions</b>		Ambient temperature			
Operation		0 ... 40 °C			
<b>Relative humidity</b>		Relative humidity			
Max. operation		90 % RH maximum (no condensation at 30 °C)			
<b>Standards</b>		<b>Standards</b>			
		Compliance with standards		CE, EAC	



Figure similar

**Article No. :** 1FL6066-1AC61-2AA1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

Rated speed	2,000 rpm
Rated torque (100 K)	8.36 Nm
Rated current	5.3 A
Rated power	1.75 kW / 2.38 hp
Max. speed	3,000 rpm
Maximum torque	25.10 Nm
Max. current	15.9 A
Static torque	11.00 Nm
Moment of inertia	22.600 kgcm <sup>2</sup>

### Physical constants

Torque constant	1.70 Nm/A
Thermal class	B (130 °C)
Net weight	11.10 kg

### Ambient conditions

Ambient temperature

Operation	0 ... 40 °C
-----------	-------------

Relative humidity

Max. operation	90 % RH maximum (no condensation at 30 °C)
----------------	--------------------------------------------

### Standards

Compliance with standards	CE, EAC
---------------------------	---------

### Mechanical data

Motor type	High Inertia
Motor type	Permanent-magnet synchronous motor
Shaft height	65
Encoder system	Incremental encoder TTL, 2500 S/R (13 bit)
Cooling	Natural cooling
Shaft end	Feather key
Radial runout tolerance	Class N
Vibration severity grade	Grade A
Degree of protection	IP65
Design acc. to Code I	IM B5 (IM V1, IM V3)
Connection type	Angular connector (rotatable)