## 6GK5108-2BD00-2AB2





SCALANCE XB108-2 unmanaged IE switch, 8x 10/100 Mbit/s Ports, 2x 100 Mbit/s multimode SC, for setting up small star and line topologies; LED diagnostics,IP20, redundant power supply, 24 V AC/DC Manual available as a download .

product type designation	SCALANCE XB108-2	
transfer rate		
transfer rate	10 Mbit/s, 100 Mbit/s	
interfaces / for communication / maximum configuration for modular devices		
number of electrical ports / maximum	8	
number of optical ports / maximum	2	
interfaces / for communication / integrated		
number of electrical connections		
<ul> <li>for network components or terminal equipment</li> </ul>	8; RJ45	
number of 100 Mbit/s SC ports		
<ul> <li>for multimode</li> </ul>	2	
interfaces / other		
number of electrical connections		
<ul><li>for power supply</li></ul>	1	
supply voltage, current consumption, power loss		
product component / connection for redundant voltage supply	Yes	
type of voltage / 1 / of the supply voltage	DC	
<ul><li>supply voltage / 1 / rated value</li></ul>	24 V	
<ul><li>power loss [W] / 1 / rated value</li></ul>	7.2 W	
<ul> <li>supply voltage / 1 / rated value</li> </ul>	19.2 28.8 V	
<ul> <li>consumed current / 1 / maximum</li> </ul>	0.3 A	
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes	
• fuse protection type / 1 / at input for supply voltage	0.6 A / 60 V	
type of voltage / 2 / of the supply voltage		
<ul><li>supply voltage / 2 / rated value</li></ul>	19.2 28.8 V	
ambient conditions		
ambient temperature		
<ul> <li>during operation</li> </ul>	0 60 °C	
during storage	-40 +80 °C	
during transport	-40 +80 °C	
relative humidity		
<ul> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %	
protection class IP	IP20	
design, dimensions and weights		
design	compact	
width	80 mm	
height	117 mm	
depth	109 mm	
net weight	0.34 kg	

fastening method	
35 mm top hat DIN rail mounting	Yes
wall mounting	No
S7-300 rail mounting	No
S7-1500 rail mounting	No
product functions / management, configuration, engineering	
product function	
<ul> <li>multiport mirroring</li> </ul>	No
• CoS	Yes
PROFINET conformity class	A
product function / switch-managed	No
product functions / redundancy	
product function	
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes
<ul> <li>Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>	No
standards, specifications, approvals	
standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
<ul> <li>for safety / from CSA and UL</li> </ul>	UL 60950-1, CSA C22.2 No. 60950-1
• for emitted interference	EN 61000-6-4 (Class B)
• for interference immunity	61000-6-2
MTBF	71 a
reference code	
according to IEC 81346-2	KF
• according to IEC 81346-2:2019	KFE
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / hazardous environments	
standard / for hazardous zone	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
certificate of suitability	OTATEAU140 A
• IECEx	Yes; IEC 60079-0, IEC 60079-15, IECEx DEK 14.0025X, Ex nA IIC T4 Gc
CCC / for hazardous zone according to GB standard	Yes
standards, specifications, approvals / other	
certificate of suitability	EN 61000-6-2, EN 61000-6-4
KC approval	Yes
Regulatory Compliance Mark (RCM)	Yes
further information / internet-Links	165
Internet-Link	
	http://www.aiomona.com/tip.polootion.tool
to web page: selection aid TIA Selection Tool     to website: Industrial communication	http://www.siemens.com/tia-selection-tool
to website: Industrial communication	http://www.siemens.com/simatic-net
to website: Industry Mall	https://mall.industry.siemens.com
to website: Information and Download Center	http://www.siemens.com/industry/infocenter
to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	2/7/2023 🖸