



Figure similar

MLFB-Ordering data

6SL3210-5FE15-0UA0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

| Rated data | | Ambient conditions | |
|-------------------------|---------------------------|----------------------------------|----------------------------------|
| Input | | Cooling | Fan |
| Number of phases | 3 AC | Installation altitude | 1000 m |
| Line voltage | 380 ... 480 V +10 % -15 % | Ambient temperature | |
| Line frequency | 45 ... 66 Hz | Operation | 0 ... 45 °C |
| Output | | Storage | -40 ... 70 °C |
| Rated power | 5.00 kW | Relative humidity | |
| Rated current (IN) | 12.60 A | Max. operation | 90 % |
| Max. output current | 37.80 A | Standards | |
| Inputs / outputs | | Compliance with standards | CE, KC, cULus, EAC, C-Tick (RCM) |

Standard digital inputs

Number 10

Digital outputs

Number 6

Analog inputs

Number 2

Analog outputs

Number 2

| Mechanical data | |
|-----------------------------|---------------------|
| Degree of protection | IP20 / UL open type |
| Frame size | F5C |
| Net weight | 5.65 kg |
| Width | 140.0 mm |
| Height | 260.0 mm |
| Depth | 240.0 mm |