

### product type designation

product description

### Flexible fiber optic trailing cable

Flexible glass fiber-optic cable, preferred length, preassembled

Flex. Fiber Optic Cable (62.5/125), Trailing cable, splittable, Pre-assembled with 4 BFOC connectors, length 3 m.



suitability for use

version of the assembled FO cable

cable designation

wire length

Flexible cable for installation in cable carriers indoors and outdoors

Assembled with four BFOC connectors

AT-W11Y(ZN)11Y 2 G 62,5/125 OM1

3 m

### optical data

attenuation factor per length

- at 850 nm / maximum
- at 1300 nm / maximum

3 dB/km

0.8 dB/km

bandwidth length product

- at 850 nm
- at 1300 nm

300 GHz·m

800 GHz·m

### mechanical data

number of fibers / per FOC core

1

number of FO cores / per FOC cable

2

version of the FO conductor fiber

Multimode graded-index fiber 62.5/125 μm, OM 1

design of the FOC core

Hollow core, filled, diameter 1400 μm

design of the fiber-optic cable

Segmentable outer conductor

outer diameter

- of the optical fibers
- of the optical fiber sheath
- of the FOC core sheath

62.5 μm

125 μm

3.5 mm

outer diameter / of the cable

12.9 mm

material

- of the fiber-optic cable core
- of the optical fiber sheath
- of the FOC core sheath
- of the fiber-optic cable sheath
- of the strain relief

Quartz glass

Quartz glass

PUR

PUR

Aramid fibers, also GRP central element

color

- of the FOC core sheath
- of cable sheath

black

Black

bending radius

- with single bend / minimum permissible
- with multiple bends / minimum permissible

150 mm

150 mm

number of bending cycles

100000

tensile load

- during installation / short-term
- during operation / maximum

2000 N

1000 N

weight per length

130 kg/km

## ambient conditions

ambient temperature	
• during operation	-30 ... +60 °C
• during storage	-30 ... +70 °C
• during transport	-30 ... +70 °C
• during installation	-30 ... +60 °C
fire behavior	flammable
chemical resistance	
• to mineral oil	acc. to IEC 60811-404 with test oil IRM 902 (acc. to ISO 1817), +100 °C, 168 h, pull speed 250 mm/min
• to grease	resistant
radiological resistance / to UV radiation	resistant
protection class IP	IP20

## product features, product functions, product components / general

product feature	
• halogen-free	Yes
• silicon-free	Yes
product component / rodent protection	No
wire length	
• for glass FOC / for 100BaseFX / for Industrial Ethernet / maximum	4000 m
• for glass FOC / for 1000BaseSX / for Industrial Ethernet / maximum	500 m
• for glass FOC / for 1000BaseLX / for Industrial Ethernet / maximum	1000 m
• for glass FOC / with PROFIBUS / maximum	3000 m

## standards, specifications, approvals

certificate of suitability	
• RoHS conformity	Yes
reference code	
• according to IEC 81346-2	WH
• according to IEC 81346-2:2019	WHA

## further information / internet-Links

Internet-Link	
• to web page: selection aid TIA Selection Tool	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>
• to website: Industrial communication	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
• to website: Industry Mall	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
• to website: Information and Download Center	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
• to website: Selection guide for cables and connectors	<a href="https://sie.ag/2QdlxcP">https://sie.ag/2QdlxcP</a>
• to website: Image database	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
• to website: CAx-Download-Manager	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

last modified: 2/14/2023 