

product type designation

product description

Flexible fiber optic trailing cable

Flexible glass fiber-optic cable, preferred length, preassembled

Flex. Fiber Optic Cable (62.5/125), Trailing cable, splittable, Pre-assembled with 4 BFOC connectors, length 75 m.



suitability for use

version of the assembled FO cable

cable designation

wire length

Flexible cable for installation in cable carriers indoors and outdoors

Assembled with four BFOC connectors

AT-W11Y(ZN)11Y 2 G 62,5/125 OM1

75 m

optical data

attenuation factor per length

- at 850 nm / maximum
- at 1300 nm / maximum

3 dB/km

0.8 dB/km

bandwidth length product

- at 850 nm
- at 1300 nm

300 GHz·m

800 GHz·m

mechanical data

number of fibers / per FOC core

1

number of FO cores / per FOC cable

2

version of the FO conductor fiber

Multimode graded-index fiber 62.5/125 μm, OM 1

design of the FOC core

Hollow core, filled, diameter 1400 μm

design of the fiber-optic cable

Segmentable outer conductor

outer diameter

- of the optical fibers
- of the optical fiber sheath
- of the FOC core sheath

62.5 μm

125 μm

3.5 mm

outer diameter / of the cable

12.9 mm

material

- of the fiber-optic cable core
- of the optical fiber sheath
- of the FOC core sheath
- of the fiber-optic cable sheath
- of the strain relief

Quartz glass

Quartz glass

PUR

PUR

Aramid fibers, also GRP central element

color

- of the FOC core sheath
- of cable sheath

black

Black

bending radius

- with single bend / minimum permissible
- with multiple bends / minimum permissible

150 mm

150 mm

number of bending cycles

100000

tensile load

- during installation / short-term
- during operation / maximum

2000 N

1000 N

weight per length

130 kg/km

ambient conditions

ambient temperature	
• during operation	-30 ... +60 °C
• during storage	-30 ... +70 °C
• during transport	-30 ... +70 °C
• during installation	-30 ... +60 °C
fire behavior	flammable
chemical resistance	
• to mineral oil	acc. to IEC 60811-404 with test oil IRM 902 (acc. to ISO 1817), +100 °C, 168 h, pull speed 250 mm/min
• to grease	resistant
radiological resistance / to UV radiation	resistant
protection class IP	IP20

product features, product functions, product components / general

product feature	
• halogen-free	Yes
• silicon-free	Yes
product component / rodent protection	No
wire length	
• for glass FOC / for 100BaseFX / for Industrial Ethernet / maximum	4000 m
• for glass FOC / for 1000BaseSX / for Industrial Ethernet / maximum	500 m
• for glass FOC / for 1000BaseLX / for Industrial Ethernet / maximum	1000 m
• for glass FOC / with PROFIBUS / maximum	3000 m

standards, specifications, approvals

certificate of suitability	
• RoHS conformity	Yes
reference code	
• according to IEC 81346-2	WH
• according to IEC 81346-2:2019	WHA

further information / internet-Links

Internet-Link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Selection guide for cables and connectors	https://sie.ag/2QdlxcP
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified: 2/14/2023 